



ARROW ENDURANCE™ Extended Dwell Peripheral Catheter System

REF **EDC-00818-B**

18 Ga. catheter | **8** cm catheter length | **.010** inch dia. wire guide

Contents:

- | | |
|--|---|
| <ul style="list-style-type: none"> 1: Catheter System: 18 Ga. (1.30 mm) x 80 mm (3.15") ARROW ENDURANCE™ over 20 Ga. (1.0 mm) HW Introducer Needle with Integral 0.010" (0.26 mm) Straight Soft Tip Wire Guide 1: Swabstick Foil Pack Skin Protectant 1: 3 mL Applicator 2% CHG and 70% IPA Chloraprep®¹ One-Step Solution with Hi-Lite Orange™ Tint 1: Drape: 24" x 36" 1: Arm Drape: 36" x 46" with 3" x 5" Fenestration 1: Label: Venous/Arterial Placement 1: Paper Tape Measure | <ul style="list-style-type: none"> 1: Tourniquet 4: Gauze Pad: 2" x 2" (5 cm x 5 cm) 4: Gauze Pad: 4" x 4" (10 cm x 10 cm) 1: Surgical Apparel: Mask 1: Dressing: Tegaderm®² 10 cm x 12 cm 1: Dressing: STATLOCK®³ Catheter Stabilization Device 1: Surgical Apparel: Bouffant Cap |
|--|---|

¹ A registered trademark of CareFusion or one of its subsidiaries.
² A registered trademark of 3M Company.
³ A registered trademark of C. R. Bard, Inc.

DuPont™ Tyvek®
packaging

Priming Volume	Gravity Flow Rate	Pump Flow Rate	MAX Injector Pressure Limit	MAX Pressure Injection Flow Rate per Injectate Viscosity		
				4.7 cP	11.8 cP	26.6 cP
0.42 mL	3682 mL/hr	11782 mL/hr	325 psi	10.0 mL/sec	8.0 mL/sec	4.5 mL/sec

Consult instructions for use for details on the testing performed to generate these values.



Caution



Consult instructions for use



Do not reuse



Do not resterilize



Sterilized by ethylene oxide



Keep away from sunlight




Keep dry



Do not use if package is damaged



Not made with natural rubber latex



Store between 15 - 30°C (59 - 86°F).
Avoid freezing and excessive heat above 40°C (104°F).

Rx only. Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death.
 Warning: This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.
 Sterile. Fluid path components are non-pyrogenic.

Manufacturer:
 Arrow International LLC
 Subsidiary of Teleflex Incorporated
 3015 Carrington Mill Blvd.
 Morrisville, NC 27560 USA

Teleflex®

www.teleflex.com

EDC-00818-201A, Rev. 2 (2020-12)

ARROW ENDURANCE™ Extended Dwell Peripheral Catheter System



REF **EDC-00818-B**

18 Ga. catheter | **8** cm catheter length | **.010** inch dia. wire guide

