





Multi-Lumen Central Venous Catheterization Kit with Blue FlexTip® Arrowg+ard Blue® Catheter



Contents:

- Multi-Lumen Indwelling Catheter: 7 Fr. x 6" (16 cm) Radiopaque Polyurethane with Blue FlexTip*, Arrowg+ard* Antimicrobial Surface Treatment¹, Extension Line Clamps
 Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End "J" Tip on Other) with Arrow Advancer
 Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer Needle
 Pressure Transduction Probe
 Initiation Normality 3 Co. x 1" (2.54 cm) and 2 cm. Lunc Lock Excitance

- 1:
- Injection Needle: 25 Ga. x 1" (2.54 cm) and 3 mL Luer-Lock Syringe Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW and 5 mL Arrow® Raulerson Spring-Wire 1: Introduction Syringe
- Injection Needle: 22 Ga. x 1-1/2" (3.81 cm) and 5 mL Luer-Slip Syringe 1:
- 1:
- 3:
- 1:
- 1:
- Injection Needle: 22 Ga. x 1-1/2" (3.81 cm) and 5 mL Luer-Slip Syringe Tissue Dilator: 8.5 Fr. (2.8 mm) x 10.2 cm Dust Cap: Non-Vented SecondSite™ Adjustable Hub: Fastener SecondSite™ Adjustable Hub: Catheter Clamp SharpsAway® Disposal Cup Drape: 21" x 36" (53 cm x 91 cm) with 3" (7.6 cm) fenestration, with adhesive Scalabel: #11 1:
- 1: Scalpel: #11
- 2:
- Gauze Pad: 2" x 2" (5 cm x 5 cm) Gauze Pad: 4" x 4" (10 cm x 10 cm) 5:
- 1: Suture: 3-0 Braided Silk with Straight Needle

¹Licensed under US Patent No. 6,706,024.


Rx only. Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death.

A California Prop. 65 Warning: Cancer and Reproductive Harm www.P65Warnings.ca.gov.

li

Fluid path components are non-pyrogenic.

Contraindications: The Arrowg+ard Blue antimicrobial catheter is contraindicated for patients with known hypersensitivity to chlorhexidine, silver sulfadiazine and/or sulfa drugs (refer to product instructions for references).



Distal (16 Ga.) Medial (18 Ga.) 0.38 1630 Proximal (18 Ga.) 0.41 1780 * Priming volumes are approximate and are done without accessories.

Priming Volume* (mL)

0.42

Gravity Flow Rate[†] (mL/hr.)

3200

Flow rates are done with deionized water or normal saline, room temperature, 100 cm head height and represent approximate flow capabilities.







*



Lumen





Manufacturer: Arrow International, Inc. Subsidiary of Teleflex Incorporated 2400 Bernville Road Reading, PA 19605 USA





