



ARROW® PICC⁺ with Chloragard® Technology

ARROW®

REF **CDA-44541-HPK1A**

4.5 Fr. | **45** cm catheter length | **.018** inch dia. spring-wire guide

ErgoPack®

Contents:

- 1: Indwelling TaperFree™ CG+™ Antimicrobial/Antithrombogenic Catheter¹: 4.5 Fr. x 45 cm Pressure Injectable Radiopaque Polyurethane with Blue FlexTip®, T-Port Connector, Extension Line Clamps, Contamination Guard and Placement Wire
- 1: GlideThru™ Peel-Away Sheath: 4.5 Fr. x 2-3/4" (7 cm) Radiopaque over 4.5 Fr. Dilator
- 1: Spring-Wire Guide, Nitinol, Marked: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other) with Arrow Advancer
- 1: Injection Needle: Eclipse™ 25 Ga. x 1" (2.54 cm) RW
- 1: Safety Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- 1: Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- 1: Syringe: 10 mL Luer-Lock
- 1: Syringe: 3 mL Luer-Lock
- 1: Dust Cap: Non-Vented
- 1: SecondSite™ Adjustable Hub: Catheter Clamp
- 1: SecondSite™ Adjustable Hub: Fastener
- 1: SharpsAway® Disposal Cup
- 1: SharpsAway II™ Locking Disposal Cup
- 1: Catheter Trimmer
- 1: Towel: 24" x 36" (61 cm x 91 cm)
- 1: Drape: 60" x 76" (152 cm x 193 cm)
- 1: Drape: 36" x 41" (91 cm x 104 cm) with 3" x 5" (8 cm x 13 cm) fenestration
- 1: Towel
- 1: Particulate Filter: 5 Micron Straw
- 1: Safety Scalpel: #11

- 1: Patient ID Card
- 1: Patient Information Booklet
- 2: Paper Tape Measure
- 1: Tourniquet
- 10: Gauze Pad: 2" x 2" (5 cm x 5 cm)
- 10: Gauze Pad: 4" x 4" (10 cm x 10 cm)
- 1: Dressing: Tegaderm™ 15.5 cm x 10 cm
- 1: Surgical Apparel: Impervious Gown
- 1: Dressing: STATLOCK™ Catheter Stabilization Device
- 1: Surgical Apparel: Mask with Eye Shield
- 1: Surgical Apparel: Bouffant Cap
- 1: Surgical Apparel: Mask
- 1: Tape: Steri-Strip™
- 1: HemoHopper™ Fluid Receptacle

¹Licensed under US Patent Nos. 6,706,024; 6,872,195 and 7,329,412.
²A trademark of Becton, Dickinson and Company.
³A registered trademark of 3M Company.
⁴A registered trademark of C. R. Bard, Inc.

All components are CE 0086 unless otherwise noted.

Contraindications: Clinical assessment of the patient must be completed to ensure no contraindications exist. The Arrow® PICC with Chloragard® Technology is contraindicated in the following areas: • Patients with known hypersensitivity to chlorhexidine • In presence of device related infections • In presence of previous or current thrombosis in the intended vessel or along the catheterized vessel pathway.


- nl** **ARROW PICC met Chloragard-technologie** Bewaren beneden 25°C. Vermijd hitte hoger dan 30°C.
- fr** **PICC ARROW avec technologie Chloragard** Conservez le produit à une température inférieure à 25°C. Veillez à ne pas exposer le produit à une chaleur excessive supérieure à 30°C.
- de** **ARROW PICC mit Chloragard-Technologie** Unter 25°C lagern. Zu hohe Temperaturen über 30°C vermeiden.
- el** **Καθετήρας ARROW PICC με Τεχνολογία Chloragard** Φυλάσσεται κάτω των 25°C. Να αποφεύγεται η υπερβολική θερμότητα άνω των 30°C.
- it** **ARROW PICC con tecnologia Chloragard** Conservare ad una temperatura inferiore a 25°C. Evitare il calore eccessivo superiore a 30°C.
- pl** **Cewnik ARROW PICC z technologią Chloragard** Przechowywać w temperaturze poniżej 25°C. Chronić przed temperaturą powyżej 30°C.
- pt** **PICC ARROW com Tecnologia Chloragard** Conservar a temperaturas inferiores a 25°C. Evitar temperaturas superiores a 30°C.
- ru** **ARROW PICC с технологией Chloragard** Хранить при температуре ниже 25°C. Избегать нагрева свыше 30°C.
- es** **PICC de ARROW con tecnología Chloragard** Almacenar a temperaturas inferiores a 25°C. Evite temperaturas excesivas por encima de 30°C.
- sv** **ARROW PICC med Chloragard-teknologi** Förvaras vid temperatur under 25°C. Undvik höga temperatur över 30°C.
- tr** **Chloragard Teknolojili ARROW PICC** 25°C'in altında saklayın. 30°C'in üzerindeki aşırı ısıdan sakının.



Not made with natural rubber latex



Store below 25°C (77°F). Avoid excessive heat above 30°C (86°F).



Lumen	Priming Volume* (mL)	Flow Rate† (mL/hr)	Pump Flow Rate‡ (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (17 Ga.)	0.50	1360	6290	5

* Priming volumes are approximate and are done without accessories.
 † Flow rates were determined using room temperature water, 100 cm head height and represent approximate flow capabilities.
 ‡ Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.
 ** Pressure injection flow rates are determined at the injector pressure setting of 300 psi maximum using media of 11.8 centipoise viscosity, with 152 cm pressure tubing.