

## REF PC-01452-W

4<sup>Fr.</sup> 2<sup>Lumen</sup> 55

## Contents: \_

- 1: Two-Lumen Indwelling Catheter: 4 Fr. x 55 cm Radiopaque Polyurethane with Blue FlexTip®, T-Port Connector, Extension Line Clamps, Contamination Guard and Placement Wire
- 2. Dust Cap: Non-Vented
- SecondSite™ Adjustable Hub: Catheter Clamp 1:
- Fastener: Catheter Clamp 1.
- SecondSite™ Adjustable Hub: Fastener 1:
- 1: Patient ID Card
- Chart Sticker 1:
- 1: Patient Information Booklet
- Paper Tape Measure

Rx only. Warning: Read all package insert warnings, cautions and instructions prior to use. Failure to do so may result in severe patient injury or death.

🗥 California Prop. 65

Warning: Cancer and Reproductive Harm www.P65Warnings.ca.gov.

Fluid path components are non-pyrogenic.

Contraindications: This device is contraindicated wherever there is presence of device related infections, previous or current thrombosis. Clinical assessment of patient must be completed to ensure no contraindications exists.




















natural rubber latex



Lumen	Priming	Flow	Pump
	Volume*	Rate <sup>†</sup>	Flow Rate <sup>‡</sup>
	(mL)	(mL/hr)	(mL/hr)
Distal (22 Ga.)	0.30	125	680
Proximal (22 Ga.)	0.40	150	900

- Priming volumes are approximate and are done without accessories.
- Flow rates are done with normal saline, room temperature, 100 cm head height and represent approximate flow capabilities.
- ‡ Pump flow rates determined at maximum pump pressure of 10 psig.

Manufacturer: Arrow International, Inc. Subsidiary of Teleflex Incorporated 2400 Bernville Road Reading, PA 19605 USA



IC-01452-101F (7/17)



