





Quad-Lumen CVC Kit



REF ASK-42854-PRJ

8.5 4 16 catheter 0.032


Contents:-

- 1: Quad-Lumen Indwelling Catheter: 8.5 Fr. x 6" (16 cm) Pressure Injectable Radiopaque Polyurethane with Blue FlexTip®, Arrowgard Blue PLUS® Antimicrobial Surface Treatment¹, **Extension Line Clamps**
- 1: Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - "J" Tip on Other) with Arrow Advancer
- 1: Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopague over 20 Ga. RW Introducer Needle
- 1: Pressure Transduction Probe
- 1: Introducer Needle: Echogenic 18 Ga. x 2-1/2" (6.35 cm) XTW and 5 mL Arrow® Raulerson Spring-Wire Introduction Syringe
- 1: Injection Needle: Eclipse^{TM2} 22 Ga. x 1-1/2" (3.81 cm) RW and 5 mL Luer-Slip Syringe
- 1: Injection Needle: Eclipse^{™2} 25 Ga. x 1" (2.54 cm) RW and 3 mL Luer-Lock Syringe

- 1: Syringe: 10 mL Luer-Lock
- 1: Tissue Dilator: 10 Fr. (3.5 mm) x 10.2 cm
- 1: SecondSite™ Adjustable Hub: Fastener
- 1: SecondSite[™] Adjustable Hub: Catheter Clamp
- 1: SharpsAway® Disposal Cup
- 1: SharpsAway II™ Locking Disposal Cup
- 1: Maximal Barrier Drape[™] with 4" fenestration
- 1: Towel
- 1: Needle Holder
- 1: Forceps
- 1: Safety Scalpel: #11 1: Checklist/CLIP Sheet
- 1: Sterile Procedure Sign
- 1: Flow Rate Information Card with Injection Log
- 2: Prep Sponge Swab
- 2: Gauze Pad: 2" x 2" (5 cm x 5 cm)

- 5: Gauze Pad: 4" x 4" (10 cm x 10 cm)
- 1: Dressing: Tegaderm^{®3} 10 cm x 12 cm
- 1: Suture: 3-0 Silk with Curved Needle
- 1: Tray: Prep
- 1: HemoHopper® Fluid Receptacle

Contraindications: The Arrowgard Blue Plus antimicrobial catheter is contraindicated for patients with known hypersensitivity to chlorhexidine, silver sulfadiazine and/or sulfa drugs (refer to product instructions for references).



Lumen	Priming Volume* (mL)	Flow Rate [†] (mL/hr)	MAX Pressure Injection Flow Rate [‡] (mL/sec)
Distal (16 Ga.)	0.38	3350	5
Medial 1 (14 Ga.)	0.45	6000	10
Medial 2 (18 Ga.)	0.35	1750	-
Proximal (18 Ga.)	0.38	1950	-

^{*} Priming volumes are approximate and are done without an injection cap.

Store below 25°C (77°F). Avoid natural rubber latex excessive heat above 40°C (104°F)

IJ-42854-100A (10/19)

¹ Licensed under US Patent Nos. 6,706,024; 6,872,195 and 7,329,412.

² A trademark of Becton, Dickinson and Company.

³ A registered trademark of 3M Company.

Based on 100 cm head height.

^{*} Pressure injection flow rates are determined using media of 11.8 centipoise viscosity, with 152 cm administration set tubing.