

Peripherally Inserted Central Catheter Kit with Blue FlexTip® Catheter

REF PK-01451

Contents:

- Indwelling Catheter: 4 Fr. x 55 cm Radiopaque Polyurethane with Blue FlexTip®, Integral Extension Line, Extension Line Clamp, Integral Suture Wing, Contamination Guard
- Peel-Away Sheath: 15 Ga. x 1-1/4" (3.18 cm) Radiopaque over 17 Ga. TW Introducer Needle
- Injection Needle: 18 Ga. x 1-1/2" (3.81 cm)
- Syringe: 10 mL Luer-Slip 1:
- Skin Protectant Prep Pad (non-sterile solution) 1:
- 3 mL Applicator 2% CHG and 70% IPA Chlora Prep $^{\circ 1}$ One-Step Solution with Hi-Lite Orange[™] Tint (non-sterile solution)
- Dust Cap: Non-Vented
- SecondSite™ Adjustable Hub: Catheter Clamp 1:
- SecondSite™ Adjustable Hub: Fastener 1:
- SharpsAway® Disposal Cup 1:
- 1: Towel
- Towel: 24" x 36" (61 cm x 91 cm)

- Drape: 24" x 36" (61 cm x 91 cm) with 4" (10 cm) fenestration
- Patient ID Card 1:
- **Chart Sticker** 1:
- Patient Information Booklet
- Dressing: OpSite®2 14 cm x 10 cm
- Paper Tape Measure
- Tourniquet
- Gauze Pad: 2" x 2" (5 cm x 5 cm)
- Gauze Pad: 4" x 4" (10 cm x 10 cm)
- Dressing: STATLOCK®3 Catheter Stabilization Device
- Surgical Apparel: Mask
- Surgical Tape: Transpore™ 1" x 54" Roll

¹A registered trademark of CareFusion or one of its subsidiaries.

²A registered trademark of T.J. Smith & Nephew, Limited.

³A registered trademark of C. R. Bard, Inc.

Rx only. Warning: Read all package insert warnings, cautions and instructions prior to use. Failure to do so may result in severe patient injury or death.

Sterilized using ethylene oxide unless otherwise indicated in the contents list.

🕂 California Prop. 65

Warning: Cancer and Reproductive Harm www.P65Warnings.ca.gov.

Fluid path components are non-pyrogenic.

Contraindications: This device is contraindicated wherever there is presence of device related infections, previous or current thrombosis. Clinical assessment of patient must be completed to ensure no contraindications exists.




















Not made with natural rubber latex



Store between 20 - 25°C (68 - 77°F). Avoid freezing and excessive heat above 40°C (104°F).



Lumen	Priming	Flow	Pump
	Volume*	Rate [†]	Flow Rate [‡]
	(mL)	(mL/hr)	(mL/hr)
Distal (18 Ga.)	0.50	850	3700

Manufacturer: Arrow International, Inc. Subsidiary of Teleflex Incorporated 2400 Bernville Road Reading, PA 19605 USA



IK-01451-101L (7/17)



Peripherally Inserted Central Catheter Kit with Blue FlexTip® Catheter



ARROV



^{*} Priming volumes are approximate and are done without accessories.
† Flow rates are done with normal saline, room temperature, 100 cm head height and represent approximate flow capabilities.

[‡] Pump flow rates are determined at maximum pump pressure of 10 psig.