



## Central Venous Catheterization Kit

**REF CK-04711** 

14<sup>Ga.</sup> 16 cm catheter length .032

inch dia.

## Contents: .

- Indwelling Catheter: 14 Ga. x 16 cm Radiopaque Polyurethane with Side Holes, Integral Suture Wing
- Spring-Wire Guide: .032" (0.81 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - "J" Tip on Other)
- Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer Needle
- Injection Needle: 22 Ga. x 1-1/2" (3.81 cm)
- Injection Needle: 25 Ga. x 1" (2.54 cm)
- Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW
- Local Anesthetic Component
- Syringe: 5 mL Luer-Slip
- Tissue Dilator: 7 Fr. (2.3 mm) x 10.2 cm

- 5 mL 1% Lidocaine HCl Solution
- 3 mL Applicator 2% CHG and 70% IPA ChloraPrep®1 One-Step Solution with Hi-Lite Orange™ Tint (non-sterile solution)
- Drape: 18" x 26" (46 cm x 66 cm) with 3" (7.6 cm) fenestration
- Scalpel: #11
- Dressing: OpSite®2 7 cm x 6 cm
- Gauze Pad: 2" x 2" (5 cm x 5 cm)
- Gauze Pad: 4" x 4" (10 cm x 10 cm)
- Suture: 3-0 Braided Silk with Straight Needle
- <sup>1</sup>A registered trademark of CareFusion or one of its subsidiaries.



















Not made with natural rubber latex



Store between 20 - 25°C (68 - 77°F).

Rx only. Warning: Read all package insert warnings, cautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. Sterilized using ethylene oxide unless otherwise indicated in the contents list.

## <u> ( California Prop. 65</u>

Warning: Cancer and Reproductive Harm www.P65Warnings.ca.gov.

Fluid path components are non-pyrogenic.

14 Ga. 2.2 mm	

Lumen	Priming Volume* (mL)	Flow Rate† (mL/hr)
Distal (14 Ga.)	0.27	7000

Friming volumes are approximate and are done without the injection cap. Injection cap priming volume is 0.17 mL.

Manufacturer: Arrow International, Inc. Subsidiary of Teleflex Incorporated 2400 Bernville Road Reading, PA 19605 USA



www.teleflex.com

IK-04711-102D (10/17)



Central Venous Catheterization Kit

6 cm catheter length .032

**REF CK-04711** 

<sup>&</sup>lt;sup>2</sup>A registered trademark of T.J. Smith & Nephew, Limited.

Flow rates are done with normal saline, room temperature, 100 cm head height and represent approximate flow capabilities.