



RFF AK-42703-CDC

7 Fr. 3 Lumen 16 cm catheter length .032

DuPont" Tyvek"

Contents: .

- 1: Multi-Lumen Indwelling Catheter: 7 Fr. x 16 cm Radiopaque Polyurethane with Blue FlexTip®, ARROWg†ard Blue PLUS® Antimicrobial Surface Treatment1, **Extension Line Clamps**
- Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - "J" Tip on Other) with Arrow Advancer™
- Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer Needle
- **Pressure Transduction Probe**
- Injection Needle: 25 Ga. x 1" (2.54 cm) 1:
- 1: 3 mL Luer-Lock Syringe
- Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW and 5 mL Arrow® Raulerson Spring-Wire Introduction Syringe
- Injection Needle: 22 Ga. x 1-1/2" (3.81 cm) and 5 mL Luer-Slip Syringe

Rx only. Warning: Read all package insert warnings, precautions and instructions prior to use

Warning: This product contains a chemical known to the State of California to cause cancer, birth

Local Anesthetic Components

All contents sterile unless otherwise indicated.

defects or other reproductive harm.

Syringe: 5 mL Luer-Slip

- 1: Tissue Dilator
- 1: 5 mL 1% Lidocaine HCl Solution
- 3 mL Applicator 2% CHG and 70% IPA ChloraPrep®2 One-Step Solution with Hi-Lite Orange[™] Tint
- Dust Cap: Non-Vented
- SecondSite™ Adjustable Hub: Fastener
- SecondSite[™] Adjustable Hub: Catheter Clamp 1:
- SharpsAway II™ Locking Disposal Cup
- Drape: 41" x 55" with 4" fenestration
- Safety Scalpel: #11 1:
- Gauze Pad: 2" x 2" (5 cm x 5 cm)
- Gauze Pad: 4" x 4" (10 cm x 10 cm)
- 1: Suture: 3-0 Braided Silk with Straight Needle

¹Licensed under US Patent Nos. 6,706,024; 6,872,195 and 7,329,412. ²A registered trademark of CareFusion or one of its subsidiaries.

Contraindications: The ARROWgʻard Blue PLUS° antimicrobial catheter technology is contraindicated for patients with known hypersensitivity to chlorhexidine, silver sulfadiazine and/or sulfa drugs (refer to product instructions for references).

Fluid path components are non-pyrogenic.

Caution



Failure to do so may result in severe patient injury or death.

instructions for use





Sterilized by ethylene oxide



from sunlight






package is damaged



natural rubber latex



Store between 20 - 25°C (68 - 77°F).



Lumen	Priming Volume* (mL)	Gravity Flow Rate [†] (mL/hr.)
Distal (16 Ga.)	0.39	3400
Medial (18 Ga.)	0.35	1800
Proximal (18 Ga.)	0.37	1900

Manufacturer: Arrow International, Inc. Subsidiary of Teleflex Incorporated 2400 Bernville Road Reading, PA 19605 USA



IK-42703-104E (1/17)



ARROWg⁺ard Blue PLUS[®] Multi-Lumen CVC Kit ARROW

Priming volumes are approximate and are done without accessories.
Flow rates are done with deionized water or norma saline, room temperature, 100 cm head height and represent approximate flow capabilities.