ARROWg⁺ard Blue PLUS[®] Two-Lumen CVC Super Kit

REF AK-45802-SK

Contents:

- 1: Two-Lumen Indwelling Catheter: 8 Fr. x 20 cm Radiopaque Polyurethane with Blue FlexTip®, ARROWg⁺ard Blue Plus® Antimicrobial Surface Treatment¹, Extension Line Clamps
- Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 23-5/8" (60 cm) (Straight 1: Soft Tip on One End - "J" Tip on Other) with Arrow Advancer
- Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer 1: Needle
- 1: Injection Needle: 25 Ga. x 1" (2.54 cm)
- Local Anesthetic Components 1:
- 1: Pressure Transduction Probe
- Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW and 5 mL Arrow® Raulerson 1: Spring-Wire Introduction Syringe
- Injection Needle: 22 Ga. x 1-1/2" (3.81 cm) and 5 mL Luer-Slip Syringe 1:
- Syringe: 3 mL Luer-Lock 1:

- Tissue Dilator: 9 Fr. (3.0 mm) x 10.2 cm 1:
- 1: 5 mL 1% Lidocaine HCI Solution
- 1: 3 mL Applicator 2% CHG and 70% IPA ChloraPrep®2 One-Step Solution with Hi-Lite Orange[™] Tint

8^{Fr.} 2^{Lumen} 20^{cm} catheter length catheter guide

- 2: Dust Cap: Non-Vented
- SecondSite[™] Adjustable Hub: Fastener 1:
- SecondSite[™] Adjustable Hub: Catheter Clamp 1:
- SharpsAway II[™] Locking Disposal Cup 1:
- Drape: 41" x 50" with 4" fenestration, with adhesive 1:
- Safety Scalpel: #11 1:
- 2: Gauze Pad: 2" x 2" (5 cm x 5 cm)
- Gauze Pad: 4" x 4" (10 cm x 10 cm) 5:
- 1: Suture: 3-0 Braided Silk with Straight Needle

¹Licensed under US Patent Nos. 6,706,024; 6,872,195 and 7,329,412. ²A registered trademark of CareFusion or one of its subsidiaries.

Contraindications: The ARROWg^{*}ard Blue PLUS[®] antimicrobial catheter technology is contraindicated for patients with known hypersensitivity to chlorhexidine, silver sulfadiazine and/or sulfa drugs (refer to product instructions for references).

Do not use if

Rx only. Warning: Read all package insert warnings, precautions and instructions prior to use Failure to do so may result in severe patient injury or death. All contents sterile unless otherwise indicated.

A California Prop. 65

Warning: Cancer and Reproductive Harm www.P65Warnings.ca.gov. Fluid path components are non-pyrogenic.

Lumen



Catheter Cross Sectior

i Consult





Do not resterilize

Gravity Flow Rate

(mL/hr.)

5600

5100



Keep away from sunlight

Keep dry package is damaged



- 25°C (77°F)

DuPont" Tyvek[®]

Store between

20 - 25°C (68 - 77°F).

Manufacturer: Arrow International, Inc. Subsidiary of Teleflex Incorporated 2400 Bernville Road Reading, PA 19605 USA

> lleleflex® www.teleflex.com


IK-45802-100G (5/17)

ARROWg⁺ard Blue PLUS® Two-Lumen CVC Super Kit



8^{Fr.} 2^{Lumen} 20^{cm}_{catheter} .032^{inch dia.} spring-wire guide

REF AK-45802-SK



Volu

(mI)

0.75