



ARROWg[†]ard Blue PLUS[®] Two-Lumen CVC Super Kit

REF AK-45802-BSK

8 r. 2 Lumen 20 cm catheter length .025

DuPont" Tyvek®

Contents:

- Two-Lumen Indwelling Catheter: 8 Fr. x 20 cm Radiopaque Polyurethane with Blue FlexTip®, ARROWg[†]ard Blue Plus® Antimicrobial Surface Treatment¹, Extension Line Clamps
- Spring-Wire Guide, Marked: .025" (0.64 mm) dia. x 23-5/8" (60 cm) (Straight Soft Tip on One End - "J" Tip on Other) with Arrow Advancer
- Catheter: 20 Ga. x 1-3/4" (4.45 cm) Radiopaque over 22 Ga. TW Introducer Needle
- Injection Needle: 25 Ga. x 1" (2.54 cm)
- Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) RW 1:
- 1: **Local Anesthetic Components**
- **Pressure Transduction Probe**
- Introducer Needle: 20 Ga. x 1-1/2" (3.81 cm) XTW and 5 mL Arrow® Raulerson Spring-Wire Introduction Syringe
- Injection Needle: 22 Ga. x 1-1/2" (3.81 cm) and 5 mL Luer-Slip Syringe
- Syringe: 3 mL Luer-Lock

- Tissue Dilator: 8.5 Fr. (2.8 mm) x 10.2 cm
- 5 mL 1% Lidocaine HCl Solution
- 3 mL Applicator 2% CHG and 70% IPA ChloraPrep®2 One-Step Solution with Hi-Lite Orange[™] Tint
- Suture: 3-0 Braided Silk with Straight Needle
- Dust Cap: Non-Vented
- SecondSite[™] Adjustable Hub: Fastener 1:
- SecondSite™ Adjustable Hub: Catheter Clamp
- SharpsAway II™ Locking Disposal Cup
- Drape: 41" x 50" with 4" fenestration, with adhesive 1:
- 1: Safety Scalpel: #11
- Gauze Pad: 2" x 2" (5 cm x 5 cm)
- Gauze Pad: 4" x 4" (10 cm x 10 cm)

¹Licensed under US Patent Nos. 6,706,024; 6,872,195 and 7,329,412. ²A registered trademark of CareFusion or one of its subsidiaries.

Contraindications: The ARROWgʻard Blue PLUS® antimicrobial catheter technology is contraindicated for patients with known hypersensitivity to chlorhexidine, silver sulfadiazine and/or sulfa drugs (refer to product instructions for references).

Rx only. Warning: Read all package insert warnings, precautions and instructions prior to use Failure to do so may result in severe patient injury or death.

^ California Prop. 65 Warning: Cancer and Reproductive Harm www.P65Warnings.ca.gov.

Fluid path components are non-pyrogenic.

All contents sterile unless otherwise indicated.



Caution

instructions for use





Sterilized by ethylene oxide








package is damaged



natural rubber latex



Store between 20 - 25°C (68 - 77°F).



Lumen	Priming Volume* (mL)	Gravity Flow Rate [†] (mL/hr.)
Distal (14 Ga.)	0.75	5600
Proximal (14 Ga.)	0.80	5100

Priming volumes are approximate and are done without accessories.

Manufacturer: Arrow International, Inc. Subsidiary of Teleflex Incorporated 2400 Bernville Road Reading, PA 19605 USA



IK-45802-101G (5/17)

ARRO\





ARROWg[†]ard Blue PLUS[®] Two-Lumen CVC Super Kit



Flow rates are done with deionized water or norma saline, room temperature, 100 cm head height and represent approximate flow capabilities.