



## **REF AK-45854-CDC**

8.5 Fr. 4 Lumen 20 cm catheter length .032 spring-wire guide

DuPont" Tyvek"

## Contents:

- 1: Quad-Lumen Indwelling Catheter: 8.5 Fr. x 20 cm Radiopaque Polyurethane with Blue FlexTip®, ARROWg†ard Blue Plus® Antimicrobial Surface Treatment1, Extension Line Clamps
- Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 23-5/8" (60 cm) (Straight Soft Tip on One End - "J" Tip on Other) with Arrow Advancer™
- Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer Needle
- **Pressure Transduction Probe**
- Injection Needle: 25 Ga. x 1" (2.54 cm) 1:
- 1: 3 mL Luer-Lock Syringe
- Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW and 5 mL Arrow® Raulerson Spring-Wire Introduction Syringe
- Injection Needle: 22 Ga. x 1-1/2" (3.81 cm) and 5 mL Luer-Slip Syringe

Rx only. Warning: Read all package insert warnings, precautions and instructions prior to use

Warning: This product contains a chemical known to the State of California to cause cancer, birth

**Local Anesthetic Components** 

All contents sterile unless otherwise indicated.

defects or other reproductive harm. Fluid path components are non-pyrogenic.

- Tissue Dilator
- 1: 5 mL 1% Lidocaine HCl Solution
- 3 mL Applicator 2% CHG and 70% IPA ChloraPrep®2 One-Step Solution with Hi-Lite Orange<sup>™</sup> Tint
- Dust Cap: Non-Vented
- SecondSite™ Adjustable Hub: Fastener
- SecondSite<sup>™</sup> Adjustable Hub: Catheter Clamp 1:
- SharpsAway II™ Locking Disposal Cup Drape: 41" x 55" with 4" fenestration
- Safety Scalpel: #11 1:
- Gauze Pad: 2" x 2" (5 cm x 5 cm)
- Gauze Pad: 4" x 4" (10 cm x 10 cm)
- 1: Suture: 3-0 Braided Silk with Straight Needle

<sup>1</sup>Licensed under US Patent Nos. 6,706,024; 6,872,195 and 7,329,412. <sup>2</sup>A registered trademark of CareFusion or one of its subsidiaries.

Contraindications: The ARROWgʻard Blue PLUS° antimicrobial catheter technology is contraindicated for patients with known hypersensitivity to chlorhexidine, silver sulfadiazine and/or sulfa drugs (refer to product instructions for references).

Caution



Failure to do so may result in severe patient injury or death.

instructions for use







Sterilized by ethylene oxide



from sunlight



Keep dry


package is damaged



natural rubber latex



Store between 20 - 25°C (68 - 77°F).



Lumen	Priming Volume* (mL)	Gravity Flow Rate <sup>†</sup> (mL/hr.)
Distal (16 Ga.)	0.43	2700
Medial 1 (14 Ga.)	0.54	5100
Medial 2 (18 Ga.)	0.36	1400
Proximal (18 Ga.)	0.41	1600

Priming volumes are approximate and are done without accessories.

Manufacturer: Arrow International, Inc. Subsidiary of Teleflex Incorporated 2400 Bernville Road Reading, PA 19605 USA



IK-45854-101G (1/17)





ARROWg<sup>+</sup>ard Blue Plus<sup>®</sup> Quad-Lumen CVC



Flow rates are done with deionized water or normal saline, room temperature, 100 cm head height and represent approximate flow capabilities.