inch dia.

DuPont<sup>™</sup> Tyvek<sup>®</sup>



## **REF AK-46702-CDC**

## Contents:

- 1: Two-Lumen Indwelling Catheter: 7 Fr. x 20 cm Radiopaque Polyurethane with Blue FlexTip®, ARROWg<sup>+</sup>ard Blue Plus® Antimicrobial Surface Treatment<sup>1</sup>, Extension Line Clamps
- Spring-Wire Guide: .032" (0.81 mm) dia. x 23-5/8" (60 cm) (Straight Soft Tip on 1: One End - "J" Tip on Other)
- Injection Needle: 25 Ga. x 1" (2.54 cm) 1:
- 1: Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW
- 1: Local Anesthetic Components
- Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer 1: Needle with 5 mL Luer-Slip Syringe
- Injection Needle: 22 Ga. x 1-1/2" (3.81 cm) and 5 mL Luer-Slip Syringe 1:
- Svringe: 3 mL Luer-Lock 1:
- Tissue Dilator: 8.5 Fr. (2.8 mm) x 10.2 cm 1:

- 5 mL 1% Lidocaine HCI Solution 1:
- 3 mL Applicator 2% CHG and 70% IPA ChloraPrep®2 One-Step Solution with 1: Hi-Lite Orange<sup>™</sup> Tint

Contraindications: The ARROWg<sup>\*</sup>ard Blue PLUS<sup>®</sup> antimicrobial catheter technology is contraindicated for patients with known hypersensitivity to chlorhexidine, silver sulfadiazine and/or sulfa drugs (refer to product instructions for references).

7<sup>Fr.</sup> 2<sup>Lumen</sup> 20<sup>cm</sup> catheter length catheter guide

- Dust Cap: Non-Vented 2.
- SecondSite<sup>™</sup> Adjustable Hub: Fastener 1:
- SecondSite<sup>™</sup> Adjustable Hub: Catheter Clamp 1:
- SharpsAway II<sup>™</sup> Locking Disposal Cup 1:
- Drape: 41" x 55" with 4" fenestration 1:
- 1: Safety Scalpel: #11
- 2: Gauze Pad: 2" x 2" (5 cm x 5 cm)
- 5: Gauze Pad: 4" x 4" (10 cm x 10 cm)
- 1: Suture: 3-0 Braided Silk with Straight Needle

<sup>1</sup>Licensed under US Patent Nos. 6,706,024; 6,872,195 and 7,329,412. <sup>2</sup>A registered trademark of CareFusion or one of its subsidiaries.

Rx only. Warning: Read all package insert warnings, precautions and instructions prior to use Failure to do so may result in severe patient injury or death. All contents sterile unless otherwise indicated.

🕂 California Prop. 65

Warning: Cancer and Reproductive Harm www.P65Warnings.ca.gov.

Lumen

Fluid path components are non-pyrogenic.



i Consult








from sunlight




- 25°C (77°F)

Store between

20 - 25°C (68 - 77°F).







Flow rates are done with deionized water or norma saline, room temperature, 100 cm head height and represent approximate flow capabilities.

Manufacturer: Arrow International, Inc. Subsidiary of Teleflex Incorporated 2400 Bernville Road Reading, PA 19605 USA



IK-46702-102F (5/17)

ARROWg<sup>+</sup>ard Blue PLUS<sup>®</sup> Two-Lumen CVC

ARRON

7<sup>Fr.</sup> 2<sup>Lumen</sup> 20<sup>cm</sup> catheter length .032<sup>inch dia.</sup> spring-wire guide



Keep away

```
Keep dry
```









package is damaged





