



REF AK-47702-CDC

7 Fr. 2 Lumen 20 cm catheter length 032 spring-wire guide

Contents: .

- Two-Lumen Indwelling Catheter: 7 Fr. x 20 cm Radiopaque Polyurethane with Blue FlexTip®, ARROWg[†]ard Blue PLUS® Antimicrobial Surface Treatment¹, Extension Line Clamps
- Spring-Wire Guide: .032" (0.81 mm) dia. x 23-5/8" (60 cm) (Straight Soft Tip on One End - "J" Tip on Other)
- Injection Needle: 25 Ga. x 1" (2.54 cm)
- Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW
- **Local Anesthetic Components**
- Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer Needle with 5 mL Luer-Slip Syringe
- Injection Needle: 22 Ga. x 1-1/2" (3.81 cm) and 5 mL Luer-Slip Syringe
- Syringe: 3 mL Luer-Lock 1:
- Tissue Dilator: 8.5 Fr. (2.8 mm) x 10.2 cm

- 5 mL 1% Lidocaine HCl Solution
- 3 mL Applicator 2% CHG and 70% IPA ChloraPrep®2 One-Step Solution with Hi-Lite Orange[™] Tint
- Dust Cap: Non-Vented
- SecondSite™ Adjustable Hub: Fastener
- SecondSite™ Adjustable Hub: Catheter Clamp
- SharpsAway II™ Locking Disposal Cup 1:
- Drape: 41" x 55" with 4" fenestration
- Safety Scalpel: #11
- 2: Gauze Pad: 2" x 2" (5 cm x 5 cm)
- Gauze Pad: 4" x 4" (10 cm x 10 cm)
- Suture: 3-0 Braided Silk with Straight Needle

¹Licensed under US Patent Nos. 6,706,024; 6,872,195 and 7,329,412. ²A registered trademark of CareFusion or one of its subsidiaries.

DuPont" Tyvek®

Rx only. Warning: Read all package insert warnings, precautions and instructions prior to use Failure to do so may result in severe patient injury or death.

All contents sterile unless otherwise indicated.

^ California Prop. 65

Warning: Cancer and Reproductive Harm www.P65Warnings.ca.gov.

Fluid path components are non-pyrogenic.



instructions for use



Do not reuse





Sterilized by ethylene oxide



from sunlight



Keep dry

package is damaged

Contraindications: The ARROWgʻard Blue PLUS® antimicrobial catheter technology is contraindicated for patients with known hypersensitivity to chlorhexidine, silver sulfadiazine and/or sulfa drugs (refer to product instructions for references).



natural rubber latex



Store between 20 - 25°C (68 - 77°F).



Lumen	Priming Volume* (mL)	Gravity Flow Rate [†] (mL/hr.)
Distal (14 Ga.)	0.57	5000
Proximal (18 Ga.)	0.40	1500

Priming volumes are approximate and are done without accessories.

Manufacturer: Arrow International, Inc. Subsidiary of Teleflex Incorporated 2400 Bernville Road Reading, PA 19605 USA



IK-47702-102F (5/17)





ARROWg⁺ard Blue PLUS[®] Two-Lumen CVC



Flow rates are done with deionized water or normal saline, room temperature, 100 cm head height and represent approximate flow capabilities.