







Arrowg+ard Blue Plus® Two-Lumen CVC

7^{Fr.} 2 Lumen 20 cm catheter length 0

spring-wire

- Two-Lumen Indwelling Catheter: 7 Fr. x 20 cm Radiopaque Polyurethane with Blue FlexTip®, Arrowg+ard Blue Plus* Antimicrobial Surface Treatment', Extension Line Clamps

 Spring-Wire Guide: .032" (0.81 mm) dia. x 23-5/8" (60 cm) (Straight Soft Tip on One End - "J" Tip on Other)
- Injection Needle: 25 Ga. x 1" (2.54 cm)
- Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW Blunt Fill Needle: 18 Ga. x 1-1/2" (3.81 cm)
- 1: Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer Needle with 5 mL Luer-Slip Syringe
 Injection Needle: 22 Ga. x 1-1/2" (3.81 cm) and 5 mL Luer-Slip Syringe

- Syringe: 3 mL Luer-Lock
 Tissue Dilator: 8.5 Fr. (2.8 mm) x 10.2 cm
 5 mL 1% Lidocaine HCI Solution and Alcohol Prep
 3 mL Applicator 2% CHG and 70% IPA ChloraPrep®2 One-Step Solution with Hi-Lite Orange™ Tint

- Dust Cap: Non-Vented
 SecondSite™ Adjustable Hub: Fastener
 SecondSite™ Adjustable Hub: Catheter Clamp
- SharpsAway II™ Locking Disposal Cup SharpsAway® Disposal Cup Drape: 41" x 55" with 4" fenestration

- Safety Scalpel: #11
- Gauze Pad: 2" x 2" (5 cm x 5 cm) Gauze Pad: 4" x 4" (10 cm x 10 cm)
- 2: Gauze Pad: 2" x 2" (5 cm x 5 cm)
 5: Gauze Pad: 4" x 4" (10 cm x 10 cm)
 1: Suture: 3-0 Braided Silk with Straight Needle


Rx only. Warning: Read all package insert warnings, cautions, and instructions prior to use. Failure to do so may result in severe patient injury or death.

\(\triangle \) California Prop. 65
Warning: Cancer and Reproductive Harm www.P65Warnings.ca.gov.

Fluid path components are non-pyrogenic.

Contraindications: The Arrowg+ard Blue Plus antimicrobial catheter is contraindicated for patients with known hypersensitivity to chlorhexidine, silver sulfadiazine and/or sulfa drugs (refer to product instructions for references).

Licensed under US Patent Nos. 6,706,024, 6,872,195 and 7,329,412.



Lumen	Priming Volume* (mL)	Gravity Flow Rate [†] (mL/hr)	
Distal (14 Ga.)	0.57	5000	
Proximal (18 Ga.)	0.40	1500	

Priming volumes are approximate and are done without accessories. Flow rates are done with deionized water or normal saline, room temperature, 100 cm head height and represent approximate flow capabilities.





















Manufacturer: Arrow International, Inc Subsidiary of Teleflex Incorporated 2400 Bernville Road Reading, PA 19605 USA



IK-47702-105A (2020-04)

REF AK-47702-CDC







