



Pressure Injectable PICC Kit with Blue FlexTip® Catheter, Seldinger Technique with 130 cm Platinum Tipped, Marked Wire

REF ASK-05052-CHM 5 Fr. 2 Lumen 500 Cm catheter length length 1018 spring-wire guide

Contents:

- Two-Lumen Indwelling Catheter: 5 Fr. x 50 cm Radiopaque Polyurethane with Blue FlexTip® and Extension Line Clamps
- GlideThru™ Peel-Away Sheath: 5 Fr. x 4" (10 cm) Radiopaque over 5 Fr. Dilator
- Spring-Wire Guide: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other)
- Spring-Wire Guide, Marked: .018" (0.46 mm) dia. x 51-3/16" (130 cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other)
- Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- Syringe: 5 mL Luer-Slip 1:
- Skin Protectant Prep Pad (non-sterile solution)

- Dust Cap: Non-Vented
- SecondSite[™] Adjustable Hub: Fastener 1:
- SecondSite™ Adjustable Hub: Catheter Clamp
- Patient ID Card 1:
- **Chart Sticker** 1:
- Patient Information Booklet 1:
- Paper Tape Measure 1:
- Dressing: STATLOCK®1 Catheter Stabilization Device

¹A registered trademark of C. R. Bard, Inc.

Rx only. Warning: Read all package insert warnings, cautions and instructions prior to use Failure to do so may result in severe patient injury or death.

Sterilized using ethylene oxide unless otherwise indicated in the contents list.

!\ California Prop. 65

Warning: Cancer and Reproductive Harm www.P65Warnings.ca.gov.

Fluid path components are non-pyrogenic.

Contraindications: This device is contraindicated wherever there is presence of device related infections, previous or current thrombosis. Clinical assessment of patient must be completed to ensure no contraindications exists.






















		_
Catheter	Cross	Section

Lumen	Priming Volume* (mL)	Flow Rate [†] (mL/hr)	Pump Flow Rate [‡] (mL/hr)	Injection Flow Rate** (mL/sec)
Distal (18 Ga.)	0.40	540	3106	4
Proximal (18 Ga.)	0.40	600	3490	4

- Priming volumes are approximate and are done without accessories.
 Flow rates were determined per BS EN ISO 10555-3:1997, Annex A using room temperature

- water, 100 cm head height and represent approximate flow capabilities.

 ** Pump flow rates are determined at maximum pump pressure of 10 psig.

 H Pressure injection flow rates are determined at the injector pressure setting of 300 psi
 maximum using media of 11.8 centipoise viscosity, with 60" extension tubing.

Manufacturer: Arrow International, Inc. Subsidiary of Teleflex Incorporated 2400 Bernville Road Reading, PA 19605 USA



IM-05052-100D (7/17)





Pressure Injectable PICC Kit with Blue FlexTip® Catheter, Seldinger Technique with 130 cm Platinum Tipped, Marked Wire