



# Pressure Injectable PICC Kit with Blue FlexTip<sup>®</sup> Catheter, Seldinger Technique with 130 cm Marked Wire

REF **ASK-05052-CHM** | 5 Fr. | 2 Lumen | 50 cm catheter length | .018 inch dia. spring-wire guide

**Contents:**

- 1: Two-Lumen Indwelling Catheter: 5 Fr. x 50 cm Radiopaque Polyurethane with Blue FlexTip<sup>®</sup> and Extension Line Clamps
- 1: GlideThru<sup>™</sup> Peel-Away Sheath: 5 Fr. x 4" (10 cm) Radiopaque over 5 Fr. Dilator
- 1: Spring-Wire Guide: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other)
- 1: Spring-Wire Guide, Marked: .018" (0.46 mm) dia. x 51-3/16" (130 cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other)
- 1: Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- 1: Syringe: 5 mL Luer-Slip
- 1: Skin Protectant Prep Pad (non-sterile solution)
- 2: Dust Cap: Non-Vented
- 1: SecondSite<sup>™</sup> Adjustable Hub: Fastener
- 1: SecondSite<sup>™</sup> Adjustable Hub: Catheter Clamp
- 1: Patient ID Card
- 1: Chart Sticker
- 1: Patient Information Booklet
- 1: Paper Tape Measure
- 1: Dressing: STATLOCK<sup>®1</sup> Catheter Stabilization Device

<sup>1</sup>A registered trademark of C. R. Bard, Inc.

Rx only. **Warning: Read all package insert warnings, cautions and instructions prior to use. Failure to do so may result in severe patient injury or death.**

Sterilized using ethylene oxide unless otherwise indicated in the contents list.

**California Prop. 65**

**Warning: Cancer and Reproductive Harm** [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Fluid path components are non-pyrogenic.


**Contraindications: The Pressure Injectable PICC is contraindicated wherever there is presence of device related infections or presence of previous or current thrombosis in the intended insertion vessel or catheter pathway. Clinical assessment of patient must be completed to ensure no contraindications exist.**



STERILE EO



Not made with natural rubber latex



Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	Pump Flow Rate‡ (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (18 Ga.)	0.40	540	3106	4
Proximal (18 Ga.)	0.40	600	3490	4

\* Priming volumes are approximate and are done without accessories.  
 † Flow rates were determined per BS EN ISO 10555-3:1997, Annex A using room temperature water, 100 cm head height and represent approximate flow capabilities.  
 ‡ Pump flow rates are determined at maximum pump pressure of 10 psig.  
 \*\* Pressure injection flow rates are determined at the injector pressure setting of 300 psi maximum using media of 11.8 centipoise viscosity, with 60" extension tubing.

Manufacturer:  
 Arrow International LLC  
 Subsidiary of Teleflex Incorporated  
 3015 Carrington Mill Blvd.  
 Morrisville, NC 27560 USA

**Teleflex<sup>®</sup>**  
[www.teleflex.com](http://www.teleflex.com)

IM-05052-100F (2021-04)



# Pressure Injectable PICC Kit with Blue FlexTip<sup>®</sup> Catheter, Seldinger Technique with 130 cm Marked Wire

REF **ASK-05052-CHM** | 5 Fr. | 2 Lumen | 50 cm catheter length | .018 inch dia. spring-wire guide