



Two-Lumen Peripherally Inserted Central Catheter Set with Blue FlexTip® Catheter Seldinger Technique with 130 cm Marked Wire



REF **PR-05052-LW** | **16**^{Ga.} | **2**^{Lumen} | **50**^{cm} catheter length | **.018**^{inch dia.} spring-wire guide

Contents:

- 1: Two-Lumen Indwelling Catheter: 16 Ga. x 50 cm Radiopaque Polyurethane with Blue FlexTip®, Extension Line Clamps
- 1: GlideThru™ Peel-Away Sheath: 5 Fr. x 4" (10 cm) Radiopaque over 5 Fr. Dilator
- 1: Spring-Wire Guide: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on Both Ends)
- 1: Spring-Wire Guide, Marked: .018" (0.46 mm) dia. x 51-3/16" (130 cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other)
- 1: Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- 1: Syringe: 5 mL Luer-Slip
- 1: Skin Protectant Prep Pad (non-sterile solution)
- 2: Dust Cap: Non-Vented
- 1: SecondSite™ Adjustable Hub: Fastener
- 1: SecondSite™ Adjustable Hub: Catheter Clamp
- 1: Patient ID Card
- 1: Chart Sticker
- 1: Patient Information Booklet
- 1: Paper Tape Measure
- 1: Dressing: STATLOCK®¹ Catheter Stabilization Device

¹A registered trademark of C. R. Bard, Inc.

Rx only. **Warning: Read all package insert warnings, cautions and instructions prior to use. Failure to do so may result in severe patient injury or death.**

California Prop. 65

Warning: Cancer and Reproductive Harm www.P65Warnings.ca.gov.

Fluid path components are non-pyrogenic.


Contraindications: The PICC is contraindicated wherever there is presence of device related infections or presence of previous or current thrombosis in the intended insertion vessel or catheter pathway. Clinical assessment of patient must be completed to ensure no contraindications exist.



STERILE EO



Not made with natural rubber latex



Lumen	Priming Volume* (mL)	Flow Rate† (mL/hr)	Pump Flow Rate‡ (mL/hr)
Distal (18 Ga.)	0.41	685	3445
Proximal (20 Ga.)	0.39	280	2016

* Priming volumes are approximate and are done without accessories.
 † Flow rates are done with normal saline, room temperature, 100 cm head height and represent approximate flow capabilities.
 ‡ Pump flow rates determined at maximum pump pressure of 10 psig.

Manufacturer:
 Arrow International LLC
 Subsidiary of Teleflex Incorporated
 3015 Carrington Mill Blvd.
 Morrisville, NC 27560 USA



IR-05052-102N (2021-04)



Two-Lumen Peripherally Inserted Central Catheter Set with Blue FlexTip® Catheter Seldinger Technique with 130 cm Marked Wire



REF **PR-05052-LW**

16^{Ga.} | **2**^{Lumen} | **50**^{cm} catheter length | **.018**^{inch dia.} spring-wire guide