

Pressure Injectable PICC Set with Blue FlexTip<sup>®</sup> Catheter and 80 cm Palladium Tipped, Marked Wire

## **REF PR-05052-HP**

## Contents: -

- 1: Two-Lumen Indwelling Catheter: 5 Fr. x 50 cm Radiopaque Polyurethane with Blue FlexTip® and Extension Line Clamps
- GlideThru<sup>™</sup> Peel-Away Sheath: 5 Fr. x 4" (10 cm) Radiopaque over 5 Fr. Dilator
- Spring-Wire Guide: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight 1: Soft Tip on Both Ends)
- Spring-Wire Guide, Marked: .018" (0.46 mm) dia. x 31-1/2" (80 cm) 1: (Straight Soft Tip on One End - Straight Stiff Tip on Other)
- 1: Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- 1: Syringe: 5 mL Luer-Slip
- Skin Protectant Prep Pad (non-sterile solution) 1:

Rx only. Warning: Read all package insert warnings, cautions and instructions prior to use. Failure to do so may result in severe patient injury or death.

Sterilized using ethylene oxide unless otherwise indicated in the contents list.

🕂 California Prop. 65

Warning: Cancer and Reproductive Harm www.P65Warnings.ca.gov.

Fluid path components are non-pyrogenic.





STERILE EO

2:

1:

1:

1:

1:








DuPont" Tyvek<sup>®</sup>

Not made with natural rubber latex



Lumen	Priming Volume* (mL)	Flow Rate <sup>†</sup> (mL/hr)	Pump Flow Rate <sup>‡</sup> (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (18 Ga.)	0.40	540	3106	4
Proximal (18 Ga.)	0.40	600	3490	4

Priming volumes are approximate and are done without accessories. Flow rates were determined per BS EN ISO 10555-3:1997, Annex A using room

Catheter Cross Section

- temperature water, 100 cm head height and represent approximate flow capabilities.
- <sup>‡</sup> Pump flow rates are determined at maximum pump pressure of 10 psig.
  \*\* Pressure injection flow rates are determined at the injector pressure setting of 300 psi maximum using media of 11.8 centipoise viscosity, with 60" pressure tubing

Manufacturer: Arrow International, Inc. Subsidiary of Teleflex Incorporated 2400 Bernville Road Reading, PA 19605 USA



IR-05052-104E (9/17)

ARRO\//



Pressure Injectable PICC Set with Blue FlexTip<sup>®</sup> Catheter and 80 cm Palladium Tipped, Marked Wire

**REF PR-05052-HP** 



SecondSite<sup>™</sup> Adjustable Hub: Fastener


- 1: Patient Information Booklet
- 1:

Dust Cap: Non-Vented

- 1: Paper Tape Measure
- 1: Dressing: STATLOCK®1 Catheter Stabilization Device
- <sup>1</sup>A registered trademark of C. R. Bard, Inc.

Contraindications: The Pressure Injectable PICC is contraindicated wherever there is presence of device related infections or presence of thrombosis in the intended insertion vessel or catheter pathway. Clinical assessment of patient must be completed to ensure no contraindications exist.

5<sup>Fr.</sup> 2<sup>Lumen</sup> 50<sup>cm</sup><sub>catheter</sub> 018<sup>inch dia.</sup> spring-wire guide



2<sup>Lumen</sup> 50<sup>cm</sup><sub>catheter</sub>