



Pressure Injectable PICC Set with Blue FlexTip® Catheter and 80 cm Marked Wire

REF **PR-05052-HP** | **5** Fr. | **2** Lumen | **50** cm catheter length | **.018** inch dia. spring-wire guide

Contents:

- | | |
|---|---|
| 1: Two-Lumen Indwelling Catheter: 5 Fr. x 50 cm Radiopaque Polyurethane with Blue FlexTip® and Extension Line Clamps | 2: Dust Cap: Non-Vented |
| 1: GlideThru™ Peel-Away Sheath: 5 Fr. x 4" (10 cm) Radiopaque over 5 Fr. Dilator | 1: SecondSite™ Adjustable Hub: Fastener |
| 1: Spring-Wire Guide: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on Both Ends) | 1: SecondSite™ Adjustable Hub: Catheter Clamp |
| 1: Spring-Wire Guide, Marked: .018" (0.46 mm) dia. x 31-1/2" (80 cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other) | 1: PICC Line Insertion Checklist |
| 1: Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW | 1: Patient ID Card |
| 1: Syringe: 5 mL Luer-Slip | 1: Chart Sticker |
| 1: Skin Protectant Prep Pad (non-sterile solution) | 1: Patient Information Booklet |
| | 1: Paper Tape Measure |
| | 1: Dressing: STATLOCK® ¹ Catheter Stabilization Device |

¹A registered trademark of C. R. Bard, Inc.

Rx only. **Warning: Read all package insert warnings, cautions and instructions prior to use. Failure to do so may result in severe patient injury or death.**

Sterilized using ethylene oxide unless otherwise indicated in the contents list.

California Prop. 65


Warning: Cancer and Reproductive Harm www.P65Warnings.ca.gov.

Fluid path components are non-pyrogenic.

Contraindications: The Pressure Injectable PICC is contraindicated wherever there is presence of device related infections or presence of previous or current thrombosis in the intended insertion vessel or catheter pathway. Clinical assessment of patient must be completed to ensure no contraindications exist.



Not made with natural rubber latex



Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	Pump Flow Rate‡ (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (18 Ga.)	0.40	540	3106	4
Proximal (18 Ga.)	0.40	600	3490	4

* Priming volumes are approximate and are done without accessories.
 † Flow rates were determined per BS EN ISO 10555-3:1997, Annex A using room temperature water, 100 cm head height and represent approximate flow capabilities.
 ‡ Pump flow rates are determined at maximum pump pressure of 10 psig.
 ** Pressure injection flow rates are determined at the injector pressure setting of 300 psi maximum using media of 11.8 centipoise viscosity, with 60" pressure tubing.

Manufacturer:
 Arrow International LLC
 Subsidiary of Teleflex Incorporated
 3015 Carrington Mill Blvd.
 Morrisville, NC 27560 USA

Teleflex®
www.teleflex.com

IR-05052-104G (2021-04)



Pressure Injectable PICC Set with Blue FlexTip® Catheter and 80 cm Marked Wire

REF **PR-05052-HP**

5 Fr. | **2** Lumen | **50** cm catheter length | **.018** inch dia. spring-wire guide