



Pressure Injectable One-Lumen PICC with 80 cm Wire

REF PR-35041-HPSM

4 Fr. | **50** cm catheter length | **.018** inch dia. spring-wire guides

Contents:


- 1: One Lumen TaperFree® Catheter: 4 Fr. (1.45 mm OD) x 50 cm, Pressure Injectable, Blue FlexTip®
- 1: GlideThru™ Peel-Away Sheath: 4 Fr. x 4" (10 cm) Radiopaque over 4 Fr. Dilator
- 1: Spring-Wire Guide: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on Both Ends)
- 1: Spring-Wire Guide, Marked: .018" (0.46 mm) dia. x 31-1/2" (80 cm)(Straight Soft Tip on One End - Straight Stiff Tip on Other)
- 1: Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- 1: Syringe: 5 mL Luer-Lock
- 1: Skin Protectant Prep
- 1: Dust Cap: Non-Vented
- 1: SecondSite™ Adjustable Hub: Catheter Clamp
- 1: SecondSite™ Adjustable Hub: Fastener
- 1: Flow Rate Information Card with Injection Log
- 1: Patient ID Card
- 1: Chart Sticker
- 1: Patient Information Booklet
- 1: Checklist/CLIP Sheet
- 1: Paper Tape Measure
- 1: Dressing: STATLOCK®¹ Catheter Stabilization Device

¹A registered trademark of C. R. Bard, Inc.

Rx only. Warning: Read all package insert warnings, precautions and instructions prior to use. Failure to do so may result in severe patient injury or death.

Fluid path components are non-pyrogenic.

Contraindications: The Pressure Injectable PICC is contraindicated wherever there is presence of device related infections or presence of previous or current thrombosis in the intended insertion vessel or catheter pathway. Clinical assessment of patient must be completed to ensure no contraindications exist.



Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	Pump Flow Rate‡ (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (17 Ga.)	0.55	1220	5740	5

* Priming volumes are approximate and are done without accessories.

† Flow rate values are approximate and are determined using deionized water at 100 cm head height.

‡ Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.

** Pressure injection flow rates are determined at the injector pressure setting of 300 psi maximum using media of 11.8 centipoise viscosity, with 152 cm pressure tubing.



Not made with natural rubber latex

Arrow International, Inc.
Subsidiary of Teleflex Incorporated
2400 Bernville Road
Reading, PA 19605 USA



www.teleflex.com

IR-35041-100D (2021-08)



REF PR-35041-HPSM

Pressure Injectable One-Lumen PICC with 80 cm Wire

4 Fr. | **50** cm catheter length | **.018** inch dia. spring-wire guides