



## Multi-Lumen Pressure Injectable PICC Set with Blue FlexTip® Catheter and 80 cm Stainless Steel Marked Wire

REF **PR-35063-HPSM** | **6** Fr. | **3** Lumen | **50** cm catheter length | **.018** inch dia. spring-wire guide

### Contents:

- |   |   |
|---|---|
| 1: Multi-Lumen Indwelling Catheter: 6 Fr. x 50 cm Pressure Injectable Radiopaque Polyurethane with Blue FlexTip®, Extension Line Clamps | 1: SecondSite™ Adjustable Hub: Fastener                           |
| 1: Peel-Away Sheath: 6.5 Fr. x 4" (10 cm) Radiopaque over 6.5 Fr. Dilator   | 1: SecondSite™ Adjustable Hub: Catheter Clamp                     |
| 1: Spring-Wire Guide: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on Both Ends)   | 1: Flow Rate Information Card with Injection Log                  |
| 1: Spring-Wire Guide, Marked: .018" (0.46 mm) dia. x 31-1/2" (80 cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other)       | 1: Patient ID Card  |
| 1: Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW   | 1: Chart Sticker  |
| 1: Syringe: 5 mL Luer-Lock  | 1: Patient Information Booklet                                    |
| 1: Skin Protectant Prep Pad (non-sterile solution)  | 1: Checklist/CLIP Sheet   |
| 3: Dust Cap: Non-Vented   | 1: Paper Tape Measure   |
|   | 1: Dressing: STATLOCK® <sup>1</sup> Catheter Stabilization Device |

<sup>1</sup>A registered trademark of C. R. Bard, Inc.

Rx only. **Warning: Read all package insert warnings, cautions and instructions prior to use. Failure to do so may result in severe patient injury or death.**

Sterilized using ethylene oxide unless otherwise indicated in the contents list.

**California Prop. 65**

**Warning: Cancer and Reproductive Harm** [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Fluid path components are non-pyrogenic.


**Contraindications: The Pressure Injectable PICC is contraindicated wherever there is presence of device related infections or presence of previous or current thrombosis in the intended insertion vessel or catheter pathway. Clinical assessment of patient must be completed to ensure no contraindications exist.**



STERILE EO



Not made with natural rubber latex



Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	Pump Flow Rate‡ (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (17 Ga.)	0.65	1320	6765	6
Medial (19 Ga.)	0.45	450	2597	not rated
Proximal (19 Ga.)	0.46	480	2579	not rated

\* Priming volumes are approximate and are done without accessories.  
 † Flow rates were determined using room temperature water, 100 cm head height and represent approximate flow capabilities.  
 ‡ Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.  
 \*\* Pressure injection flow rates are determined at the injector pressure setting of 300 psi maximum using media of 11.8 centipoise viscosity, with 152 cm pressure tubing.

Manufacturer:  
 Arrow International, Inc.  
 Subsidiary of Teleflex Incorporated  
 2400 Bernville Road  
 Reading, PA 19605 USA

**Teleflex®**  
[www.teleflex.com](http://www.teleflex.com)

IR-35063-100D (2020-06)



## Multi-Lumen Pressure Injectable PICC Set with Blue FlexTip® Catheter and 80 cm Stainless Steel Marked Wire

REF **PR-35063-HPSM**

**6** Fr. | **3** Lumen | **50** cm catheter length | **.018** inch dia. spring-wire guide