



## Pressure Injectable PICC Set with Blue FlexTip® Catheter and 80 cm Stainless Steel Marked Wire

**REF PR-35541-HPSM**

**4** Fr. | **55** cm catheter length | **.018** inch dia. spring-wire guide

**Contents:**

- 1: Indwelling TaperFree™ Catheter: 4 Fr. x 55 cm Pressure Injectable Radiopaque Polyurethane with Blue FlexTip® and Extension Line Clamp
- 1: GlideThru™ Peel-Away Sheath: 4 Fr. x 4" (10 cm) Radiopaque over 4 Fr. Dilator
- 1: Spring-Wire Guide: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on Both Ends)
- 1: Spring-Wire Guide, Marked: .018" (0.46 mm) dia. x 31-1/2" (80 cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other)
- 1: Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- 1: Syringe: 5 mL Luer-Lock
- 1: Skin Protectant Prep Pad (non-sterile solution)
- 1: Dust Cap: Non-Vented
- 1: SecondSite™ Adjustable Hub: Catheter Clamp
- 1: SecondSite™ Adjustable Hub: Fastener
- 1: Flow Rate Information Card with Injection Log
- 1: Patient ID Card
- 1: Chart Sticker
- 1: Patient Information Booklet
- 1: Checklist/CLIP Sheet
- 1: Paper Tape Measure
- 1: Dressing: STATLOCK®<sup>1</sup> Catheter Stabilization Device

<sup>1</sup>A registered trademark of C. R. Bard, Inc.


**Rx only. Warning: Read all package insert warnings, cautions and instructions prior to use. Failure to do so may result in severe patient injury or death.**

**California Prop. 65 Warning: Cancer and Reproductive Harm**  
[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Sterilized using ethylene oxide unless otherwise indicated in the contents list.

Fluid path components are non-pyrogenic.

**Contraindications: The Pressure Injectable PICC is contraindicated wherever there is presence of device related infections or presence of previous or current thrombosis in the intended insertion vessel or catheter pathway. Clinical assessment of patient must be completed to ensure no contraindications exist.**



Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	Pump Flow Rate‡ (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (17 Ga.)	0.58	1140	5720	5

\* Priming volumes are approximate and are done without injection caps.

† Flow rates were determined using room temperature water, 100 cm head height and represent approximate flow capabilities.

‡ Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.

\*\* Pressure injection flow rates are determined at the injector pressure setting of 300 psi maximum using media of 11.8 centipoise viscosity, with 152 cm pressure tubing.



Not made with natural rubber latex

Arrow International, Inc.  
 Subsidiary of Teleflex Incorporated  
 2400 Bernville Road  
 Reading, PA 19605 USA



www.teleflex.com

IR-35541-100D (2020-05)



**REF PR-35541-HPSM**

## Pressure Injectable PICC Set with Blue FlexTip® Catheter and 80 cm Stainless Steel Marked Wire

**4** Fr. | **55** cm catheter length | **.018** inch dia. spring-wire guide