



Pressure Injectable PICC Set with Blue FlexTip® Catheter and 130 cm Stainless Steel Marked Wire

REF **PR-35563-HPSL** | **6** Fr. | **3** Lumen | **55** cm catheter length | **.018** inch dia. spring-wire guide

Contents:

- 1: Multi-Lumen Indwelling Catheter: 6 Fr. x 55 cm Pressure Injectable Radiopaque Polyurethane with Blue FlexTip®
- 1: Peel-Away Sheath: 6.5 Fr. x 4" (10 cm) Radiopaque over 6.5 Fr. Dilator
- 1: Spring-Wire Guide: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on Both Ends)
- 1: Spring-Wire Guide, Marked: .018" (0.46 mm) dia. x 51-3/16" (130cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other)
- 1: Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- 1: Syringe: 5 mL Luer-Lock
- 1: Skin Protectant Prep Pad (non-sterile solution)
- 3: Dust Cap: Non-Vented
- 1: SecondSite™ Adjustable Hub: Fastener
- 1: SecondSite™ Adjustable Hub: Catheter Clamp
- 1: Flow Rate Information Card with Injection Log
- 1: Patient ID Card
- 1: Chart Sticker
- 1: Patient Information Booklet
- 1: Checklist/CLIP Sheet
- 1: Paper Tape Measure
- 1: Dressing: STATLOCK®¹ Catheter Stabilization Device

¹A registered trademark of C. R. Bard, Inc.

Rx only. **Warning: Read all package insert warnings, cautions and instructions prior to use. Failure to do so may result in severe patient injury or death.**

Sterilized using ethylene oxide unless otherwise indicated in the contents list.

California Prop. 65

Warning: Cancer and Reproductive Harm www.P65Warnings.ca.gov.

Fluid path components are non-pyrogenic.


Contraindications: The Pressure Injectable PICC is contraindicated wherever there is presence of device related infections or presence of previous or current thrombosis in the intended insertion vessel or catheter pathway. Clinical assessment of patient must be completed to ensure no contraindications exist.



STERILE EO



Not made with natural rubber latex



Lumen	Priming Volume* (mL)	Flow Rate† (mL/hr)	Pump Flow Rate‡ (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (17 Ga.)	0.71	1070	5976	6
Medial (19 Ga.)	0.46	360	2246	not rated
Proximal (19 Ga.)	0.49	390	2467	not rated

* Priming volumes are approximate and are done without injection caps.

† Flow rates were determined using room temperature water, 100 cm head height and represent approximate flow capabilities.

‡ Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.

** Pressure injection flow rates are determined at the injector pressure setting of 300 psi maximum using media of 11.8 centipoise viscosity, with 152 cm pressure tubing.

Manufacturer:
Arrow International, Inc.
Subsidiary of Teleflex Incorporated
2400 Bernville Road
Reading, PA 19605 USA

Teleflex®
www.teleflex.com

IR-35563-101D (2020/05)



Pressure Injectable PICC Set with Blue FlexTip® Catheter and 130 cm Stainless Steel Marked Wire

REF **PR-35563-HPSL**

6 Fr. | **3** Lumen | **55** cm catheter length | **.018** inch dia. spring-wire guide