







## **REF PR-41541-BAS**

4.5 Fr. 15 cm catheter length 018 spring-wire quide

## Arrowg+ard Blue Advance™ Midline

## Contents:

- TaperFree® Catheter with Arrowg+ard Blue Advance™ Antimicrobial/Antithrombogenic Protection<sup>1</sup>: 4.5 Fr. x 15 cm Pressure Injectable with Blue FlexTip® Feature
- GlideThru™ Peel-Away Sheath: 4.5 Fr. x 2-3/4" (7 cm) Radiopaque over 4.5 Fr. Dilator
- Spring-Wire Guide, Nitinol, Marked: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other)
- Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- Syringe: 10 mL Luer-Lock
- 1: Dust Cap: Non-Vented
- SecondSite™ Adjustable Hub: Catheter Clamp
- SecondSite™ Adjustable Hub: Fastener

- SharpsAway® Disposal Cup
- SharpsAway II™ Locking Disposal Cup 1:
- Catheter Trimmer 1:
- Safety Scalpel: #11 1:
- Patient ID Card
- Patient Information Booklet
- Flow Rate Information Card with Injection Log
- Paper Tape Measure 1:
- Dressing: STATLOCK®2 Catheter Stabilization

<sup>1</sup>Licensed under US Patent Nos. 6,706,024; 6,872,195 and 7,329,412.

<sup>2</sup>A registered trademark of C. R. Bard, Inc.



Lumen	Priming Volume* (mL)	Flow Rate <sup>†</sup> (mL/hr)	Flow Rate <sup>‡</sup> (mL/hr)	Injection Flow Rate** (mL/sec)
Distal	0.31	2420	8820	5

- Based on 100 cm head height.
- Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.
- \* Pressure injection flow rates are determined using media of 11.8 centipoise viscosity, with 152 cm adminstration set tubing

Rx only. Warning: Read all package insert warnings, cautions and instructions prior to use. Failure to do so may result in severe patient injury or death.

🗥 California Prop. 65

Warning: Cancer and Reproductive Harm www.P65Warnings.ca.gov.

Fluid path components are non-pyrogenic.

Contraindications: The Arrowg+ard Blue Advance Pressure Injectable Midline is contraindicated for patients with known hypersensitivity to chlorhexidine.



















Avoid excessive heat above 30°C (86°F).

Manufacturer: Arrow International, Inc. Subsidiary of Teleflex Incorporated

