



REF JRT-43541-HPHNM



# Arrow+ard Blue Advance™ JACC

## Contents:

- 1: TaperFree® Catheter with Arrow+ard Blue Advance™ Antimicrobial/Antithrombogenic Protection<sup>1</sup>: 4.5 Fr. x 35 cm Pressure Injectable
- 1: GlideThru™ Peel-Away Sheath: 4.5 Fr. x 4" (10 cm) Radiopaque over 4.5 Fr. Dilator
- 1: Guidewire, Nitinol, Marked: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other)
- 1: Guidewire, Marked: .018" (0.46 mm) dia. x 80 cm Hydrophilic-Coated Nitinol with Soft Tip Tungsten Coil
- 1: Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- 1: Syringe: 10 mL Luer-Lock
- 1: Dust Cap: Non-Vented
- 1: SecondSite™ Adjustable Hub: Catheter Clamp
- 1: SecondSite™ Adjustable Hub: Fastener
- 1: Catheter Trimmer

- 1: Safety Scalpel: #11
- 1: TightTrack™ Tunneler: 9" Stainless Steel
- 1: Patient ID Card
- 1: Chart Sticker
- 1: Patient Information Booklet
- 1: Flow Rate Information Card with Injection Log
- 1: Paper Tape Measure
- 1: Dressing: Tegaderm®<sup>2</sup> 10 cm x 12 cm

<sup>1</sup>Licensed under US Patent Nos. 6,706,024; 6,872,195 and 7,329,412.  
<sup>2</sup>A registered trademark of 3M Company.



STERILE EO



Not made with natural rubber latex

Store below 25°C (77°F).  
Avoid excessive heat above 30°C (86°F).


Rx only. **Warning: Read all package insert warnings, cautions and instructions prior to use. Failure to do so may result in severe patient injury or death.**

**California Prop. 65**

**Warning: Cancer and Reproductive Harm** [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Fluid path components are non-pyrogenic.

**Contraindications: The Arrow+ard Blue Advance antimicrobial/antithrombogenic catheter is contraindicated for patients with known hypersensitivity to chlorhexidine.**



Lumen	Priming Volume* (mL)	Flow Rate† (mL/hr)	Pump Flow Rate‡ (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (17 Ga.)	0.44	1415	5913	5

\* Priming volumes are approximate and are done without accessories.  
 † Based on 100 cm head height.  
 ‡ Fluid resuscitation flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.  
 \*\* Pressure injection flow rates are determined using media of 11.8 centipoise viscosity, with 152 cm administration set tubing.

**Manufacturer:**  
 Arrow International, Inc.  
 Subsidiary of Teleflex Incorporated  
 2400 Bernville Road  
 Reading, PA 19605 USA

**Teleflex®**  
[www.teleflex.com](http://www.teleflex.com)

IR-43541-100B (01/19)