




ARROW® PICC with Chloragard® Technology

4.5 Fr. | 55 cm catheter length | .018 inch dia. guide wire | 80 cm Hydrophilic-Coated Nitinol Guidewire

REF PR-45541-HPHNM

Contents:

- ① **1: Indwelling TaperFree™ CG+™ Antimicrobial/Antithrombogenic Catheter¹: 4.5 Fr. x 55 cm Pressure Injectable Radiopaque Polyurethane with Blue FlexTip®, Extension Line Clamp and Contamination Guard**
- ② **1: GlideThru™ Peel-Away Sheath: 4.5 Fr. x 4" (10 cm) Radiopaque over 4.5 Fr. Dilator**
- ③ **1: Guidewire, Marked: .018" (0.46 mm) dia. x 80 cm Hydrophilic-Coated Nitinol with Soft Tip Tungsten Coil**
- ④ **1: Guidewire, Marked: .018" (0.46 mm) dia. x 17-3/4" (45 cm) Nitinol (Straight Soft Tip on One End – Straight Stiff Tip on Other)**
- ⑤ **1: Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW**
- ⑥ **1: Syringe: 10 mL Luer-Lock**
1: Skin Protectant Prep Pad
1: Dust Cap: Non-Vented
- ⑦ **1: SecondSite™ Adjustable Hub: Catheter Clamp and Fastener**
- ⑧ **1: Catheter Trimmer**
- ⑨ **1: Safety Scalpel: #11**
1: Chart Sticker
1: Checklist/CLIP Sheet
1: Flow Rate Information Card with Injection Log
1: Patient ID Card
1: Patient Information Booklet
- ⑩ **1: Dressing: STATLOCK®^{Q2} Catheter Stabilization Device**
1: Paper Tape Measure
¹ Licensed under US Patent Nos. 6,706,024; 6,872,195 and 7,329,412.
² A registered trademark of C. R. Bard, Inc.



Caution



Do not reuse



Do not resterilize

STERILE EO

Sterilized by ethylene oxide



Keep away from sunlight



Keep dry



Do not use if package is damaged



Is not made with natural rubber latex



Consult instructions for use

Rx only. Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death.

Contraindications: The Arrow® PICC with Chloragard® Technology is contraindicated for patients with known hypersensitivity to chlorhexidine (refer to product instructions for references).

Sterile. Fluid path components are non-pyrogenic.



Lumen	Priming Volume* (mL)	Flow Rate† (mL/hr)	Pump Flow Rate‡ (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (17 Ga.)	0.59	1100	5130	5

* Priming volumes are approximate and are done without injection caps.

† Flow rates were determined using room temperature water, 100 cm head height and represent approximate flow capabilities.

‡ Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.

** Pressure injection flow rates are determined at the injector pressure setting of 300 psi maximum using media of 11.8 centipoise viscosity, with 152 cm pressure tubing.

ARROW
INTERNATIONAL

2400 Bernville Road
Reading, PA 19605 USA
www.arrowintl.com



Store below 25°C (77°F).
Avoid excessive heat above 30°C (86°F).