

REF PS-01452-NM 4^{Fr.} 2 Lumen 50 catheter catheter

Contents: _

- 1: Two-Lumen Indwelling Catheter: 4 Fr. x 50 cm Radiopaque Polyurethane with Blue FlexTip®, Extension Line Clamps
- Peel-Away Sheath: 15 Ga. x 1-1/4" (3.18 cm) Radiopague 1: over 17 Ga. TW Introducer Needle
- 2. Dust Cap: Non-Vented
- 1: SecondSite™ Adjustable Hub: Catheter Clamp
- SecondSite™ Adjustable Hub: Fastener 1.
- 1: Drape: 18" x 26" (46 cm x 66 cm) with 3" (7.6 cm)
- Dressing: STATLOCK®1 Catheter Stabilization Device 1:

¹A registered trademark of C. R. Bard, Inc.

Rx only.

Warning: Read all package insert warnings, cautions, and instructions prior to use. Failure to do so may result in severe patient injury or death.

Contraindications: The PICC is contraindicated wherever there is presence of device related infections or presence of previous or current thrombosis in the intended insertion vessel or catheter pathway. Clinical assessment of patient must be completed to ensure no contraindications exist.

California Prop. 65 Warning: Cancer and Reproductive Harm www.P65Warnings.ca.gov.


Fluid path components are non-pyrogenic.











Not made with natural rubber latex

Catheter Cross Section

Lumen	Priming Volume* (mL)	Flow Rate [†] (mL/hr)	Pump Flow Rate [‡] (mL/hr)
Distal (22 Ga.)	0.27	250	1440
Proximal (22 Ga.)	0.33	210	1520

- Priming volumes are approximate and are done without accessories. Flow rates are done with normal saline, room temperature, 100 cm head
- height and represent approximate flow capabilities.

 ‡ Pump flow rates determined at maximum pump pressure of 10 psig.

Manufacturer: Arrow International, Inc. Subsidiary of Teleflex Incorporated 2400 Bernville Road Reading, PA 19605 USA



IS-01452-100D (3/18)



REF PS-01452-NM 4 Fr. 2 Lumen

Contents: -

- 1: Two-Lumen Indwelling Catheter: 4 Fr. x 50 cm Radiopaque Polyurethane with Blue FlexTip®, Extension Line Clamps
- Peel-Away Sheath: 15 Ga. x 1-1/4" (3.18 cm) Radiopague 1: over 17 Ga. TW Introducer Needle
- 2. Dust Cap: Non-Vented
- 1: SecondSite™ Adjustable Hub: Catheter Clamp
- SecondSite™ Adjustable Hub: Fastener 1.
- 1: Drape: 18" x 26" (46 cm x 66 cm) with 3" (7.6 cm)
- Dressing: STATLOCK®1 Catheter Stabilization Device 1:

Rx only.

Warning: Read all package insert warnings, cautions, and instructions prior to use. Failure to do so may result in severe patient injury or death.

Contraindications: The PICC is contraindicated wherever there is presence of device related infections or presence of previous or current thrombosis in the intended insertion vessel or catheter pathway. Clinical assessment of patient must be completed to ensure no contraindications exist.

California Prop. 65 Warning: Cancer and Reproductive Harm www.P65Warnings.ca.gov.

Fluid path components are non-pyrogenic.









STERILE EO









Not made with natural rubber latex

22Ga 4 Fr. 1.4 mm 22 Ga Catheter Cross Section

Priming Pump Flow Rate[‡] Flow Rate† Volume (mL) (mL/hr) (mL/hr) Lumen Distal (22 Ga.) 0.27 250 1440 Proximal (22 Ga.) 210 1520 0.33

- Priming volumes are approximate and are done without accessories.
 Flow rates are done with normal saline, room temperature, 100 cm head
- height and represent approximate flow capabilities.

 ‡ Pump flow rates determined at maximum pump pressure of 10 psig.

Manufacturer: Arrow International, Inc. Subsidiary of Teleflex Incorporated 2400 Bernville Road Reading, PA 19605 USA



IS-01452-100D (3/18)



ARROW® PICC Set



REF PS-01452-NM 4 Fr. 2 Lumen



ARROW® PICC Set



REF PS-01452-NM 4 Fr. 2 Lumen

¹A registered trademark of C. R. Bard, Inc.