

REF PS-01651-NM
ARROW® PICC Set
ARROW®

Contents:

- 1: Indwelling Catheter: 16 Ga. x 50 cm Radiopaque Polyurethane with Blue FlexTip®, Integral Extension Line, Extension Line Clamp, Injection Site Cap, Integral Suture Wing, Contamination Guard
- 1: Peel-Away Catheter: 14 Ga. x 2-1/2" (6.35 cm) Radiopaque over 15 Ga. TW Introducer Needle and 3 mL Luer-Slip Syringe
- 1: SecondSite™ Adjustable Hub: Fastener
- 1: SecondSite™ Adjustable Hub: Catheter Clamp
- 1: Drape: 18" x 26" with 3" fenestration
- 1: Dressing: STATLOCK®¹ Catheter Stabilization Device

¹A registered trademark of C. R. Bard, Inc.

Catheter Diameter: 16Ga., 1.75 mm

Priming Volume: 0.64 mL

Priming volumes are approximate and are done without the injection cap. Injection cap priming volume is 0.17 mL.

Flow Rate: 1850 mL/hr

Flow rates are with normal saline, room temperature, 100 cm head height and represent approximate flow capabilities.

Pump Flow Rate: 8070 mL/hr

Pump flow rates determined at maximum pump pressure of 10 psig.

Rx only. Warning: Read all package insert warnings, cautions, and instructions prior to use. Failure to do so may result in severe patient injury or death.

Sterile. Do not reuse — do not resterilize. Sterilized by ethylene oxide. Keep away from sunlight. Keep dry. Do not use if package has been previously opened or damaged. Not made with natural rubber latex. Consult instructions for use. Fluid path components are non-pyrogenic.

Manufacturer:
 Arrow International, Inc.
 2400 Bemville Road
 Reading, PA 19605 USA
 www.arrowintl.com



ISO 01651:03B, Rev.1 (3/16)

REF PS-01651-NM
ARROW® PICC Set
ARROW®

Contents:

- 1: Indwelling Catheter: 16 Ga. x 50 cm Radiopaque Polyurethane with Blue FlexTip®, Integral Extension Line, Extension Line Clamp, Injection Site Cap, Integral Suture Wing, Contamination Guard
- 1: Peel-Away Catheter: 14 Ga. x 2-1/2" (6.35 cm) Radiopaque over 15 Ga. TW Introducer Needle and 3 mL Luer-Slip Syringe
- 1: SecondSite™ Adjustable Hub: Fastener
- 1: SecondSite™ Adjustable Hub: Catheter Clamp
- 1: Drape: 18" x 26" with 3" fenestration
- 1: Dressing: STATLOCK®¹ Catheter Stabilization Device

¹A registered trademark of C. R. Bard, Inc.

Catheter Diameter: 16Ga., 1.75 mm

Priming Volume: 0.64 mL

Priming volumes are approximate and are done without the injection cap. Injection cap priming volume is 0.17 mL.

Flow Rate: 1850 mL/hr

Flow rates are with normal saline, room temperature, 100 cm head height and represent approximate flow capabilities.

Pump Flow Rate: 8070 mL/hr

Pump flow rates determined at maximum pump pressure of 10 psig.

Rx only. Warning: Read all package insert warnings, cautions, and instructions prior to use. Failure to do so may result in severe patient injury or death.

Sterile. Do not reuse — do not resterilize. Sterilized by ethylene oxide. Keep away from sunlight. Keep dry. Do not use if package has been previously opened or damaged. Not made with natural rubber latex. Consult instructions for use. Fluid path components are non-pyrogenic.

Manufacturer:
 Arrow International, Inc.
 2400 Bemville Road
 Reading, PA 19605 USA
 www.arrowintl.com



ISO 01651:03B, Rev.1 (3/16)

