

REF PS-01652-NM

ARROW® PICC Set

ARROW®

Contents:

- 1: Two-Lumen Indwelling Catheter: 16 Ga. x 50 cm Radiopaque Polyurethane with Blue FlexTip®, Contamination Guard
- 1: Peel-Away Catheter: 14 Ga. x 2-1/2" (6.35 cm) Radiopaque over 15 Ga. TW Introducer Needle and 3 mL Luer-Slip Syringe
- 1: Injection Site Cap
- 2: Clamp: Extension Lines
- 1: SecondSite™ Adjustable Hub: Fastener
- 1: SecondSite™ Adjustable Hub: Catheter Clamp
- 1: Drape: 18" x 26" with 3" fenestration
- 1: Dressing: STATLOCK® Catheter Stabilization Device

¹A registered trademark of C. R. Bard, Inc.

Catheter Diameter: 16Ga., 1.7 mm

Lumen	Priming Volume* (mL)	Flow Rate† (mL/hr)	Pump Flow Rate‡ (mL/hr)
Distal	0.42	449	3440
Proximal	0.43	178	2010

* Priming volumes are approximate and are done without the injection cap. Injection cap priming volume is 0.17 mL.

† Flow rate values are approximate and are determined using deionized water at 100 cm head height.

‡ Pump flow rates determined at maximum pump pressure of 10 psig.

Rx only. Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death.

Sterile. Do not reuse — do not resterilize. Sterilized by ethylene oxide. Keep away from sunlight. Keep dry. Do not use if package has been previously opened or damaged. Not made with natural rubber latex. Consult instructions for use. Fluid path components are non-pyrogenic.

Manufacturer:
Arrow International, Inc.
2400 Bernville Road
Reading, PA 19605 USA
www.arrowintl.com



ISO16521-102C (04/19)

REF PS-01652-NM

ARROW® PICC Set

ARROW®

Contents:

- 1: Two-Lumen Indwelling Catheter: 16 Ga. x 50 cm Radiopaque Polyurethane with Blue FlexTip®, Contamination Guard
- 1: Peel-Away Catheter: 14 Ga. x 2-1/2" (6.35 cm) Radiopaque over 15 Ga. TW Introducer Needle and 3 mL Luer-Slip Syringe
- 1: Injection Site Cap
- 2: Clamp: Extension Lines
- 1: SecondSite™ Adjustable Hub: Fastener
- 1: SecondSite™ Adjustable Hub: Catheter Clamp
- 1: Drape: 18" x 26" with 3" fenestration
- 1: Dressing: STATLOCK® Catheter Stabilization Device

¹A registered trademark of C. R. Bard, Inc.

Catheter Diameter: 16Ga., 1.7 mm

Lumen	Priming Volume* (mL)	Flow Rate† (mL/hr)	Pump Flow Rate‡ (mL/hr)
Distal	0.42	449	3440
Proximal	0.43	178	2010

* Priming volumes are approximate and are done without the injection cap. Injection cap priming volume is 0.17 mL.

† Flow rate values are approximate and are determined using deionized water at 100 cm head height.

‡ Pump flow rates determined at maximum pump pressure of 10 psig.

Rx only. Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death.

Sterile. Do not reuse — do not resterilize. Sterilized by ethylene oxide. Keep away from sunlight. Keep dry. Do not use if package has been previously opened or damaged. Not made with natural rubber latex. Consult instructions for use. Fluid path components are non-pyrogenic.

Manufacturer:
Arrow International, Inc.
2400 Bernville Road
Reading, PA 19605 USA
www.arrowintl.com



ISO16521-102C (04/19)

LOT

Use By

Date of Manufacture

LOT

Use By

Date of Manufacture