

ARROW® PICC powered by ARROW_® VPS[®] Stylet



REF CDC-34052-VPS

5 Fr. 2 Lumen 40 cm catheter length .018 inch dia. spring-wire length



Contents:

- 1: Two-Lumen Indwelling TaperFree™ Catheter: 5 Fr. x 40 cm Pressure Injectable Radiopaque Polyurethane with Blue FlexTip®, Extension Line Clamps, Contamination Guard, Arrow® VPS® Stylet and Tuohy-Borst Adapter
- 1: GlideThru™ Peel-Away Sheath: 5 Fr. x 2-3/4" (7 cm) Radiopague over 5 Fr. Dilator
- Placement Wire Assembly
- 1: Spring-Wire Guide, Nitinol, Marked: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other) with Arrow
- 1: Injection Needle: SafetyGlide™1 25 Ga. x 5/8" (1.60 cm) RW
- Safety Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- Blunt Fill Needle: 18 Ga. x 1-1/2" (3.81 cm)
- Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- 1: Syringe: 10 mL Luer-Lock
- Syringe: 3 mL Luer-Lock
- Skin Protectant Prep Pad (non-sterile solution)
- 10 mL Luer-Lock Pre-Filled Saline Syringe
- 5 mL 1% Lidocaine HCl Solution and Alcohol Prep (non-sterile solution)
- 3 mL Applicator 2% CHG and 70% IPA ChloraPrep®2 One-Step Solution (non-sterile solution)

- 1: 3 mL Applicator 2% CHG and 70% IPA ChloraPrep®² One-Step Solution with Hi-Lite Orange™ Tint (non-sterile solution)
- Dust Cap: Non-Vented
- SecondSite™ Adjustable Hub: Fastener SecondSite™ Adjustable Hub: Catheter Clamp
- SharpsAway® Disposal Cup
- SharpsAway II™ Locking Disposal Cup
- Catheter Trimmer
- Towel: 24" x 36" (61 cm x 91 cm)
- Drape: 60" x 76" (152 cm x 193 cm)
- Drape: 36" x 41" (91 cm x 104 cm) with 3" x 5" (8 cm x 13 cm) fenestration
- Towel
- Safety Scalpel: #11
- Flow Rate Information Card with Injection Log
- Sterile Procedure Sign
- Patient ID Card
- Chart Sticker
- Patient Information Booklet
- Medication Label: 1% Lidocaine
- Checklist/CLIP Sheet
- 2: Paper Tape Measure

- Tourniquet
 Foam Electrodes (3 per pack)
- 10: Gauze Pad: 2" x 2" (5 cm x 5 cm)
- 10: Gauze Pad: 4" x 4" (10 cm x 10 cm)
- 1: Dressing: Tegaderm^{®3} 15.5 cm x 10 cm
- Surgical Apparel: Impervious Gown Dressing: BIOPATCH®4
- Dressing: STATLOCK® Catheter Stabilization Device
- Surgical Apparel: Mask with Eve Shield
- Surgical Apparel: Bouffant Cap
- Surgical Apparel: Mask
- Tape: Steri-Strip®3 HemoHopper® Fluid Receptacle
- Console Pointers
- 1: Marker

Lumen

Distal (18 Ga.)

Proximal (18 Ga.)

- ¹A trademark of Becton, Dickinson and Company.
- ²A registered trademark of CareFusion or one of its subsidiaries.
- ³A registered trademark of 3M Company.
 ⁴A registered trademark of Johnson & Johnson Corporation.

Priming

Volume

(mL)

0.44

0.44


⁵A registered trademark of C. R. Bard, Inc.

Sterilized using ethylene oxide unless otherwise indicated in the contents list. Contraindications: The Pressure Injectable PICC is contraindicated wherever there is presence of device related infections

or presence of thrombosis in the intended insertion vessel or catheter pathway. Clinical assessment of patient must be completed to ensure no contraindications exist.

Warning: The results of certain animal experiments have shown phthalates to be potentially toxic to reproduction. 185 mm Proceeding from the present state of scientific knowledge, risks for male premature infants cannot be excluded in the case of long-term exposure or application. Medical products containing phthalates should be used only temporarily with pregnant women, nursing mothers, babies and infants.

Arrow International provides the enclosed medication label(s) for your convenience. Please ensure that these labels are applied to the correct syringe and corresponding medication.



Catheter Cross Section

-	
*	Priming volumes are approximate and are done without accessories.
†	Flow rates were determined using room temperature water, 100 cm head height and represent

approximate flow capabilities. [‡] Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.

Flow

Rate[†]

(mL/hr)

860

860

Pump

Flow Rate[‡]

(mL/hr)

4720

4680

** Pressure injection flow rates are determined at the injector pressure setting of 300 psi maximum using media of 11.8 centipoise viscosity, with 152 cm pressure tubing.

	/	1	
No	t mac	le wi	th
natur	al rub	ber l	atex



Contains Phthalate: DEHP



Store between 20-25°C (68-77°F)

IV-34052-115A (01/19)

MAX Pressure

Injection

Flow Rate**

(mL/sec)

5

5