





6 catheter length

spring-wire guide

## Two-Lumen Central Venous Catheterization Kit with Blue FlexTip® Catheter

- Two-Lumen Catheter: 7 Fr. (2.5 mm OD) x 16 cm Spring-Wire Guide, Marked: 0.25" (0.64 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End "J" Tip on Other) with Arrow Advancer
- Catheter: 20 Ga. x 1-3/4" (4.45 cm) Radiopaque over 22 Ga. TW Introducer Needle Injection Needle: 22 Ga. x 1-1/2" (3.81 cm) Introducer Needle: 20 Ga. x 1-1/2" (3.81 cm) Introducer Needle: 20 Ga. x 1-1/2" (3.81 cm) XTW Injection Needle: 25 Ga. x 1" (2.54 cm)

- Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) RW

- Pressure Transduction Probe
  Syringe: 3 mL Luer-Lock
  Syringe: 5 mL Luer-Slip
  Arrow® Raulerson Spring-Wire Introduction Syringe: 5 mL
  Tissue Dilator: 8.5 Fr. (2.8 mm) x 10.2 cm

- Dust Cap: Non-Vented
  Dust Cap: Non-Vented
  Dust Cap: Non-Vented
  SecondSite™ Adjustable Hub: Fastener
  SecondSite™ Adjustable Hub: Catheter Clamp
  SharpsAway® Disposal Cup

- Drape: 19-5/8" x 29-1/2" (50 cm x 75 cm) with adhesive Drape: 21" x 36" (53 cm x 91 cm) with 3" (7.6 cm) fenestration, with adhesive Scalpei: #11
  Stopcock: 4-way High-Flow

- Stopbook. 4-way high-how Prep Sponge Swab Gauze Pad: 2" x 2" (5 cm x 5 cm) Gauze Pad: 4" x 4" (10 cm x 10 cm) Suture: 3-0 Braided Silk with Straight Needle Tray: Prep

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death.

California Prop. 65

A WARNING: Cancer and Reproductive Harm.
www.P65Warnings.ca.gov

Not made with natural rubber latex.

Fluid path components are non-pyrogenic.



Lumen	Priming Volume* (mL)	Flow Rate† (mL/hr)
Distal (18 Ga.)	0.34	1500
Proximal (14 Ga.)	0.51	5000

<sup>\*</sup> Priming volumes are approximate and are done without accessories

† Based on 100 cm head height.





















LotNumber



YYYY-MM-DĐ



(01)XXXXXXXXXXXXXXX (17)YYMMDD (10)LotNumber

Arrow International, Inc. Subsidiary of Teleflex Incorporated 2400 Bernville Road Reading, PA 19605 USA



LBL011024 (06/20)









