







16 cm catheter length

Multi-Lumen Central Venous Catheterization Kit with Blue FlexTip® ARROWg+ard Blue® Catheter

- Multi-Lumen Indwelling Catheter: 7 Fr. x 6" (16 cm) Radiopaque Polyurethane with Blue FlexTip®, ARROWg+ard® Antimicrobial Surface Treatment¹, Extension Line Clamps
- Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 17-3/4" (45 cm) (Straight Soft
- Tip on One End "J" Tip on Other) with Arrow Advancer Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer Needle
- Pressure Transduction Probe
- Injection Needle: 25 Ga. x 1" (2.54 cm) and 3 mL Luer-Lock Syringe Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW and 5 mL Arrow® Raulerson Spring-Wire Introduction Syringe
 Injection Needle: 22 Ga. x 1-1/2" (3.81 cm) and 5 mL Luer-Slip Syringe
 Tissue Dilator: 8.5 Fr. (2.8 mm) x 10.2 cm

- Dust Cap: Non-Vented
 SecondSite™ Adjustable Hub: Fastener
 SecondSite™ Adjustable Hub: Catheter Clamp
- SharpsAway® Disposal Cup
- Drape: 21" x 36" (53 cm x 91 cm) with 3" (7.6 cm) fenestration, with adhesive Scalpel: #11

- Gauze Pad: 2" x 2" (5 cm x 5 cm)
 Gauze Pad: 4" x 4" (10 cm x 10 cm)
 Suture: 3-0 Braided Silk with Straight Needle

¹Licensed under US Patent No. 6,706,024

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death.

California Prop. 65

www.P65Warnings.ca.gov

Not made with natural rubber latex.

Store between 20 - 25°C (68 - 77°F).

Fluid path components are non-pyrogenic.

Contraindications: The Arrowg+ard Blue antimicrobial catheter is contraindicated for patients with known hypersensitivity to chlorhexidine, silver sulfadiazine and/or sulfa drugs (refer to product instructions for references).

	16 Ga	
7 Fr. 2.4 mm	18 Ga.	18Ga.

Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)
Distal (16 Ga.)	0.42	2656
Medial (18 Ga.)	0.38	1353
Proximal (18 Ga.)	0.41	1477

^{*} Priming volumes are approximate and are done without accessories.






































[†] Flow rate values are approximate and are determined using deionized water at 100 cm head height.