



**REF SA-12703** 

 $7^{\text{Fr.}}$   $3^{\text{Lumen}}$ 

16 cm catheter length

.032 inch dia. spring-wire guide

## **Three-Lumen CVC**

## Contents:

- Three-Lumen Catheter: 7 Fr. (2.5 mm OD) x 16 cm
- Spring-Wire Guide, Nitinol, Marked: .032" (0.81 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End "J" Tip on Other) with Arrow Advancer Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer
- Introducer Needle: Echogenic 18 Ga. x 2-1/2" (6.35 cm) XTW Pressure Transduction Probe

- Pressure Transduction Probe

  Arrow® Raulerson Spring-Wire Introduction Syringe: 5 mL

  Tissue Dilator: 8.5 Fr. (2.8 mm) x 10.2 cm

  SecondSite™ Adjustable Hub: Fastener

  SecondSite™ Adjustable Hub: Catheter Clamp

  Drape: 29-1/2" x 35-1/2" (75 cm x 90 cm) with 4" (10 cm) fenestration, with
- Drape: 19-5/8" x 29-1/2" (50 cm x 75 cm) with adhesive Safety Scalpel: #11

- Prep Sponge Swab

  Valve: MicroCLAVE™1 Neutral Displacement Connector

<sup>1</sup>A trademark of ICU Medical, Inc.

All components are CE 2797 unless otherwise noted.

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU Not made with natural rubber latex. Fluid path components are non-pyrogenic.

Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	
Distal (16 Ga.)	0.4	2947	
Medial (18 Ga.)	0.4	1552	
Proximal (18 Ga.)	0.4	1702	

<sup>\*</sup> Priming volumes are approximate and are done without accessories.



LOT



M













**EU Authorized** Representative and Importer:




Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA



LBL050064 R01 (2023-09)









.032 inch dia. spring-wire guide





<sup>†</sup> Flow rate values are approximate and are determined using deionized water at 100 cm head height.