



REF SA-12802

8 Fr. 2 Lumen 16 cm catheter length .032 inch dia. spring-wire guide

Two-Lumen CVC

Contents:

- 1: Two-Lumen Catheter: 8 Fr. (2.8 mm OD) x 16 cm
- 1: Spring-Wire Guide, Nitinol, Marked: .032" (0.81 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - "J" Tip on Other) with Arrow Advancer
- 1: Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer Needle
- 1: Introducer Needle: Echogenic 18 Ga. x 2-1/2" (6.35 cm) XTW
- 1: Pressure Transduction Probe
- 1: Arrow® Raulerson Spring-Wire Introduction Syringe: 5 mL
- 1: Tissue Dilator: 9 Fr. (3.0 mm) x 10.2 cm
- 1: SecondSite™ Adjustable Hub: Fastener
- 1: SecondSite™ Adjustable Hub: Catheter Clamp
- 1: Drape: 29-1/2" x 35-1/2" (75 cm x 90 cm) with 4" (10 cm) fenestration, with adhesive
- 2: Drape: 19-5/8" x 29-1/2" (50 cm x 75 cm) with adhesive
- 1: Safety Scalpel: #11
- 2: Prep Sponge Swab
- 2: Valve: MicroCLAVE™¹ Neutral Displacement Connector

¹A trademark of ICU Medical, Inc.

All components are CE 2797 unless otherwise noted.

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU

Not made with natural rubber latex.

Fluid path components are non-pyrogenic.



Lumen

Priming Volume^{*} (mL)

Gravity Flow Rate[†] (mL/hr)



Lumen	Priming Volume [*] (mL)	Gravity Flow Rate [†] (mL/hr)
Distal (14 Ga.)	0.66	5279
Proximal (14 Ga.)	0.71	4764

* Priming volumes are approximate and are done without accessories.

† Flow rate values are approximate and are determined using deionized water at 100 cm head height.



LOT



EU Authorized Representative and Importer:

EC REP
2797
Teleflex Medical
IDA Business and
Technology Park
Dublin Road, Athlone
Co. Westmeath, Ireland

Arrow International LLC
Subsidiary of Teleflex Incorporated
3015 Carrington Mill Blvd.
Morrisville, NC 27560 USA

Teleflex
www.teleflex.com

LBL050067 R01 (2023-09)



REF SA-12802

8 Fr. 2 Lumen 16 cm catheter length .032 inch dia. spring-wire guide

Two-Lumen CVC