



REF SA-12853

8.5 Fr. **3** Lumen

16 cm catheter length

.032 inch dia. spring-wire guide

Three-Lumen CVC

Contents:

- Three-Lumen Catheter: 8.5 Fr. (3.0 mm OD) x 16 cm
- Spring-Wire Guide, Nitinol, Marked: .032" (0.81 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End "J" Tip on Other) with Arrow Advancer Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer
- Introducer Needle: Echogenic 18 Ga. x 2-1/2" (6.35 cm) XTW Pressure Transduction Probe

- Pressure Transduction Probe

 Arrow® Raulerson Spring-Wire Introduction Syringe: 5 mL

 Tissue Dilator: 9 Fr. (3.0 mm) x 10.2 cm

 SecondSite™ Adjustable Hub: Fastener

 SecondSite™ Adjustable Hub: Catheter Clamp

 Drape: 29-1/2" x 35-1/2" (75 cm x 90 cm) with 4" (10 cm) fenestration, with adhesive

- adhesive
 Drape: 19-5/8" x 29-1/2" (50 cm x 75 cm) with adhesive
 Safety Scalpel: #11
 Prep Sponge Swab
 Valve: MicroCLAVETM1 Neutral Displacement Connector

¹A trademark of ICU Medical, Inc.

All components are CE 2797 unless otherwise noted.

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe

injury or death. www		ly result in severe patient
Not made with natura	al rubber latex.	
Fluid path components	s are non-pyrogenic.	

Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)		
Distal (16 Ga.) Medial (14 Ga.) Proximal (16 Ga.)	0.41 0.81 0.44	3137 7038 3021		

^{*} Priming volumes are approximate and are done without accessories.



LOT





M



















Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA



LBL050070 R01 (2023-09)











.032 inch dia. spring-wire guide



[†] Flow rate values are approximate and are determined using deionized water at 100 cm head height.