



REF SA-15955

9.5 Fr. 5 Lumen

20 cm catheter length

.032 inch dia. spring-wire guide

Five-Lumen CVC

Contents:

- Five-Lumen Catheter: 9.5 Fr. (3.3 mm OD) x 20 cm
- Spring-Wire Guide, Nitinol, Marked: .032" (0.81 mm) dia. x 23-5/8" (60 cm) (Straight Soft Tip on One End "J" Tip on Other) with Arrow Advancer with
- Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer Needle
- Introducer Needle: Echogenic 18 Ga. x 2-1/2" (6.35 cm) XTW

- Introducer Needle: Ecnogenic 18 Ga. x 2-1/2" (6.35 cm) X I W
 Pressure Transduction Probe
 Arrow® Raulerson Spring-Wire Introduction Syringe: 5 mL
 Tissue Dilator: 10 Fr. (3.5 mm) x 10.2 cm
 SecondSite ™ Adjustable Hub: Fastener
 SecondSite ™ Adjustable Hub: Catheter Clamp
 Drape: 29-1/2" x 35-1/2" (75 cm x 90 cm) with 4" (10 cm) fenestration, with
 adhesive adhesive
 Drape: 19-5/8" x 29-1/2" (50 cm x 75 cm) with adhesive
- Safety Scalpel: #11
- Prep Sponge Swab

 Valve: MicroCLAVE™¹ Neutral Displacement Connector
- ¹A trademark of ICU Medical, Inc.

All components are CE 2797 unless otherwise noted.

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU Not made with natural rubber latex. Fluid path components are non-pyrogenic.

Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	
Distal (16 Ga.)	0.48	2988	
Medial 1 (14 Ga.)	0.57	4474	
Medial 2 (18 Ga.)	0.38	1038	
Medial 3 (18 Ga.)	0.38	963	
Proximal (18 Ga.)	0.41	1204	

^{*} Priming volumes are approximate and are done without accessories.

















EU Authorized Representative and Importer



Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA




LBL050092 R01 (2023-09)



LOT











 $[\]dagger$ Flow rate values are approximate and are determined using deionized water at 100 cm head height.