



REF EU-25854-EN

8.5 Fr. 4 Lumen 20 cm catheter length .032 inch dia. spring-wire guide

# Arrowg+ard Blue® Four-Lumen CVC

**Contents:**

- 1: Arrowg+ard Blue® Four-Lumen Catheter: 8.5 Fr. (3.0 mm OD) x 20 cm
- 1: Spring-Wire Guide, Nitinol, Marked: .032" (0.81 mm) dia. x 23-5/8" (60 cm) (Straight Soft Tip on One End - "J" Tip on Other) with Arrow Advancer with ECG Mark
- 1: Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW
- 1: Pressure Transduction Probe
- 1: Arrow® Raulerson Spring-Wire Introduction Syringe: 5 mL
- 1: Tissue Dilator: 10 Fr. (3.5 mm) x 10.2 cm
- 1: SecondSite™ Adjustable Hub: Fastener
- 1: SecondSite™ Adjustable Hub: Catheter Clamp

All components are CE 2797 unless otherwise noted.

**Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. [www.teleflex.com/IFU](http://www.teleflex.com/IFU)**

**Not made with natural rubber latex.**

Store below 25°C (77°F). Avoid excessive heat above 40°C (104°F). Fluid path components are non-pyrogenic.

**Contraindications: The Arrowg+ard Blue antimicrobial catheter is contraindicated for patients with known hypersensitivity to chlorhexidine, silver sulfadiazine and/or sulfa drugs.**



CAS # 7440-48-4



Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)
Distal (16 Ga.)	0.45	2108
Medial 1 (14 Ga.)	0.58	3860
Medial 2 (18 Ga.)	0.39	1096
Proximal (18 Ga.)	0.40	1129

\* Priming volumes are approximate and are done without accessories.

† Flow rate values are approximate and are determined using deionized water at 100 cm head height.

EU Authorized Representative and Importer:

Teleflex Medical  
IDA Business and Technology Park  
Dublin Road, Athlone  
Co. Westmeath, Ireland

Arrow International LLC  
Subsidiary of Teleflex Incorporated  
3015 Carrington Mill Blvd.  
Morrisville, NC 27560 USA

Teleflex®  
[www.teleflex.com](http://www.teleflex.com)

LBL051245 R01 (2023-11)

LOT



8.5 Fr. 4 Lumen 20 cm catheter length .032 inch dia. spring-wire guide

REF EU-25854-EN

Arrowg+ard Blue® Four-Lumen CVC