





7 Fr. **2** Lumen

Arrowg+ard Blue Plus® Two-Lumen CVC

- Contents:

 1: Arrowg+ard Blue Plus®¹ Two-Lumen Catheter: 7 Fr. (2.5 mm OD) x 20 cm

 1: Spring-Wire Guide: .032" (0.81 mm) dia. x 23-5/8" (60 cm) (Straight Soft Tip on One End "J" Tip on Other)

 1: Injection Needle: 25 Ga. x 1" (2.54 cm)

 1: Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW

 1: Blunt Fill Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW

 1: Blunt Fill Needle: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer Needle with 5 mL Luer-Slip Syringe

 1: Injection Needle: 22 Ga. x 1-1/2" (3.81 cm) and 5 mL Luer-Slip Syringe

 1: Syringe: 3 mL Luer-Lock

 1: Tissue Dilator: 8.5 Fr. (2.8 mm) x 10.2 cm

 1: 5 mL 1% Lidocaine HCl Solution and Alcohol Prep

 1: 3 mL Applicator 2% CHG and 70% IPA ChloraPrep®2 One-Step Solution with Hi-Lite Orange™ Tint

 2: Dust Cap: Non-Vented

 1: SecondSite™ Adjustable Hub: Fastener

 1: SecondSite™ Adjustable Hub: Catheter Clamp

 1: SharpsAway® II Locking Disposal Cup

 1: SharpsAway® Disposal Cup

 1: Drape: 41" x 55" with 4" fenestration

۷.	Gauze	rau.	_	^	_
5.	Gauze	Pad:	4"	x	4

- 1: Safety Scalpel: #11
 2: Gauze Pad: 2" x 2" (5 cm x 5 cm)
 5: Gauze Pad: 4" x 4" (10 cm x 10 cm)
 1: Suture: 3-0 Braided Silk with Straight Needle
- Licensed under US Patent No. 7,329,412.

 A registered trademark of CareFusion or one of its subsidiaries.

Rx only
Warning: Read all package insert warnings, precautions, and
instructions prior to use. Failure to do so may result in severe patient
injury or death.
California Prop. 65

Injury or dearn.

California Prop. 65

MARNING: Cancer and Reproductive Harm.

www.P65Warnings.ca.gov

Not made with natural rubber latex.

Store between 20 - 25°C (68 - 77°F).

Sterilized using ethylene oxide unless otherwise indicated in the contents

Contraindications: The Arrowg+ard Blue Plus antimicrobial catheter is contraindicated for patients with known hypersensitivity to chlorhexidine, silver sulfadiazine and/or sulfa drugs.

^{*} Priming volumes are approximate and are done without accessories.









Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA



LBL051354 R01 (2022-02)









 $[\]ensuremath{\dagger}$ Flow rate values are approximate and are determined using deionized water at 100 cm head height.