20 cm catheter length









(IPNXXXXXX)



Pressure Injectable Arrowg+ard Blue Plus® Two-Lumen CVC

- Arrowg+ard Blue Plus®1 Two-Lumen Catheter: 8 Fr. (2.8 mm OD) x 20 cm, Pressure Injectable
- Spring-Wire Guide, Nitinol, Marked: .032" (0.81 mm) dia. x 23-5/8" (60 cm) (Straight Soft Tip on One End "J" Tip on Other) with Arrow Advancer with ECG Mark
- Introducer Needle: Echogenic 18 Ga. x 2-1/2" (6.35 cm) XTW
- Pressure Transduction Probe
 Arrow® Raulerson Spring-Wire Introduction Syringe: 5 mL
- Tissue Dilator: 9 Fr. (3.0 mm) x 10.2 cm

- Dust Cap: Non-Vented
 SecondSite™ Adjustable Hub: Fastener
 SecondSite™ Adjustable Hub: Catheter Clamp
- SharpsAway® II Locking Disposal Cup Safety Scalpel: #11

Licensed under US Patent No. 7.329 412

All components are CE 2797 unless otherwise noted.

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU Not made with natural rubber latex.

Store below 25°C (77°F). Avoid excessive heat above 40°C

Fluid path components are non-pyrogenic.

Contraindications: The Arrowg+ard Blue Plus antimicrobial catheter is contraindicated for patients with known hypersensitivity to chlorhexidine, silver sulfadiazine and/or sulfa drugs.

Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (14 Ga.)	0.73	5354	10
Proximal (14 Ga.)	0.75	3984	10





(AS # 7440-48-4)

Representative and Importer: Importer:

Teleflex Medical IDA Business and Technology Park
Dublin Road, Athlone
Co. Westmeath, Ireland


All components are CE 2797 unless otherwise noted.

Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA

Product of xxx

Teleflex®

LBL051632 R02 (2024-11)



LOT Lot Number





(01)XXXXXXXXXXXXXXX (17)YYMMDD (11)YYMMDD (10)Lot Number











[†] Flow rate values are approximate and are determined using deionized water at 100 cm head height.

^{**} Pressure injection flow rates are determined using media of 11.8 centipoise (cP) viscosity, with 152 cm administration set tubing.