ARRC





(IPNXXXXXX)

8 cm catheter length

■018 inch dia. spring-wire guide

Arrowg+ard Blue® Two-Lumen CVC

- Arrowg+ard Blue® Two-Lumen Catheter: 4 Fr. (1.5 mm OD) x 8 cm Spring-Wire Guide, Nitinol, Marked: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End "J" Tip on Other) with Arrow Advancer
- Catheter: 22 Ga. x 1-3/4" (4.45 cm) Radiopaque over 25 Ga. RW Introducer Needle
- Introducer Needle: 20 Ga. x 1-1/2" (4 cm) XTW
- Syringe: 5 mL Luer-Slip Tissue Dilator: 5 Fr. (1.8 mm) x 7.5 cm
- Tissue Dilator: 5 Fr. (1.8 mm) x 4.1 cm
 SecondSite™ Adjustable Hub: Catheter Clamp
 SecondSite™ Adjustable Hub: Fastener
- SharpsAway® II Locking Disposal Cup
- Safety Scalpel: #11

All components are CE 2797 unless otherwise noted.

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU Not made with natural rubber latex.

Store below 25°C (77°F). Avoid excessive heat above 40°C (104°F). Fluid path components are non-pyrogenic.

Contraindications: The Arrowg+ard Blue antimicrobial catheter is contraindicated for patients with known hypersensitivity to chlorhexidine, silver sulfadiazine and/or sulfa drugs.

















el hu is











| Lumen | Priming Volume* (mL) | Flow Rate† (mL/hr) | |
|--|----------------------------|--------------------------|--|
| Distal (22 Ga.) Proximal (22 Ga.) | 0.3 0.3 | 581 317 | |
| * Priming volumes are approximate and are done without accessories | | | |

Gravity



EU Authorized Representative and Importer:



IDA Business and Technology Park Dublin Road, Athlone 2797 Co. Westmeath, Ireland


All components are CE 2797 unless otherwise noted.

Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA

Product of xxx Packaged in xxx









(01)XXXXXXXXXXXXXXX (17)YYMMDD (11)YYMMDD (10)LotNumber

1feleflex® www.teleflex.com

LBL051754 R02 (2024-08)



8 cm catheter length

.018 inch dia. spring-wire guide







Flow rate values are approximate and are determined using deionized water at 100 cm head height.