

REF AK-25703-A 7^{Fr.} **3**^{Lumen}



Arrowg+ard Blue® Three-Lumen CVC

Contents:

1.

- 1: 1:
- Arrowg+ard Blue® Three-Lumen Catheter: 7 Fr. (2.5 mm OD) x 20 cm Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 23-5/8" (60 cm) (Straight Soft Tip on One End "J" Tip on Other) with Arrow Advancer Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer Needle
- Drape: 24" x 36" (61 cm x 91 cm) with 4" (10 cm) fenestration
 Scalpel: #11
 Gauze Pad: 2" x 2" (5 cm x 5 cm)
 Gauze Pad: 4" x 4" (10 cm x 10 cm)
 Suture: 3-0 Braided Silk with Straight Needle
 A registered trademark of CareFusion or one of its subsidiaries.

20 cm catheter _032 inch dia. spring-wire guide

- Carnetel I's Ga. X 2-1/2 (c.35 cm) Radiopaque over 20 Ga. RW introducer Needle
 Injection Needle: 25 Ga. x 1" (2.54 cm)
 Pressure Transduction Probe
 Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW and 5 mL Arrow® Raulerson Spring-Wire Introduction Syringe
 Injection Needle: 22 Ga. x 1-1/2" (3.81 cm) and 5 mL Luer-Slip Syringe
 Syringe: 3 mL Luer-Lock
 5 mL 1% Lidocaine HCI Solution and Alcohol Prep
 3 mL Applicator 2% CHG and 70% IPA ChloraPrep®1 One-Step Solution with Hi-Lite Orange™ Tint
 Dust Cap: Non-Vented
 SecondSite™ Adjustable Hub: Fastener
 SecondSite™ Adjustable Hub: Catheter Clamp
 SharpsAway® Disposal Cup

Rx only Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. California Prop. 65 California Prop. 65 & WARNING: Cancer and Reproductive Harm. www.P65Warnings.ca.gov Not made with natural rubber latex. Store between 20 - 25°C (68 - 77°F). Sterilized using ethylene oxide unless otherwise indicated in the contents list

Fluid path components are non-pyrogenic Contraindications: The Arrowg+ard Blue antimicrobial catheter is contraindicated for patients with known hypersensitivity to chlorhexidine, silver sulfadiazine and/or sulfa drugs.

Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	
Distal (16 Ga.)	0.4	2258	
Medial (18 Ga.)	0.4	1046	
Proximal (18 Ga.)	0.4	1154	

* Priming volumes are approximate and are done without accessories.
 † Flow rate values are approximate and are determined using deionized water at 100 cm head height.

LOT

 \Box

Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA

> **Teleflex**® LBL052069 R01 (2022-02)



[] [M]

REF AK-25703-A





Arrowg+ard Blue® Three-Lumen CVC