



REF ASK-12703-PCA1 (IPNXXXXXX)



7 Fr. 3 Lumen 16 cm catheter length .032 inch dia. spring-wire guide

Pressure Injectable Three-Lumen CVC Kit



Contents:

- 1: Three-Lumen Catheter: 7 Fr. (2.5 mm OD) x 16 cm, Pressure Injectable

1: Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - "J" Tip on Other) with Arrow Advancer

1: Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer Needle

1: Pressure Transduction Probe

1: Introducer Needle: Echogenic 18 Ga. x 2-1/2" (6.35 cm) XTW and 5 mL Arrow® Raulerson Spring-Wire Introduction Syringe

1: Injection Needle: Eclipse™1 23 Ga. x 1-1/2" (3.81 cm) and 5 mL Luer-Slip Syringe

1: Injection Needle: Eclipse™1 25 Ga. x 1" (2.54 cm) and 3 mL Luer-Lock Syringe

1: Syringe: 10 mL Luer-Lock

1: Tissue Dilator: 8.5 Fr. (2.8 mm) x 10.2 cm

1: SecondSite™ Adjustable Hub: Fastener

1: SecondSite™ Adjustable Hub: Catheter Clamp

1: SharpsAway® II Locking Disposal Cup

1: SharpsAway® Disposal Cup

1: Maximal Barrier Drape™ with 4" fenestration

1: Towel

1: Needle Holder

1: Safety Scalpel: #11

1: Flow Rate Information Card with Injection Log

1: Checklist/CLIP Sheet

1: Sterile Procedure Sign

2: Gauze Pad: 3" x 3" (7.6 cm x 7.6 cm)

2: Gauze Pad: 2" x 2" (5 cm x 5 cm)
- 5: Gauze Pad: 4" x 4" (10 cm x 10 cm)

1: PICC/CVC Securement Device (5.1 cm x 5.4 cm) and CHG I.V. Securement Dressing (8.5 cm x 11.5 cm)

1: Suture: 3-0 Silk with Curved Needle

3: Valve: MaxZero™2 Needleless Connector

1: HemoHopper® Fluid Receptacle

¹A trademark of Becton, Dickinson and Company.

²A trademark of CareFusion or one of its subsidiaries.

Not made with natural rubber latex.



Lumen	Priming Volume† (mL)	Gravity Flow Rate† (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (16 Ga.)	0.4	2947	10
Medial (18 Ga.)	0.4	1552	5
Proximal (18 Ga.)	0.4	1702	5

* Priming volumes are approximate and are done without accessories.
† Flow rate values are approximate and are determined using deionized water at 100 cm head height.
** Pressure injection flow rates are determined using media of 11.8 centipoise (cP) viscosity, with 152 cm administration set tubing.

