



REF ASK-45703-PRJ (IPNXXXXXX)

7 Fr. 3 Lumen

20 cm catheter length

.032 inch dia. spring-wire guide



Pressure Injectable Arrowg+ard Blue Plus® Three-Lumen CVC Kit



Contents:

- 1: Arrowg+ard Blue Plus®¹ Three-Lumen Catheter: 7 Fr. (2.5 mm OD) x 20 cm, Pressure Injectable

1: Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 23-5/8" (60 cm) (Straight Soft Tip on One End - "J" Tip on Other) with Arrow Advancer

1: Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer Needle

1: Pressure Transduction Probe

1: Introducer Needle: Echogenic 18 Ga. x 2-1/2" (6.35 cm) XTW and 5 mL Arrow® Raulerson Spring-Wire Introduction Syringe

1: Injection Needle: Eclipse™² 23 Ga. x 1-1/2" (3.81 cm) and 5 mL Luer-Slip Syringe

1: Injection Needle: Eclipse™² 25 Ga. x 1" (2.54 cm) and 3 mL Luer-Lock Syringe

1: Syringe: 10 mL Luer-Lock

1: Tissue Dilator: 8.5 Fr. (2.8 mm) x 10.2 cm

1: SecondSite™ Adjustable Hub: Fastener

1: SecondSite™ Adjustable Hub: Catheter Clamp

1: SharpsAway® II Locking Disposal Cup

1: SharpsAway® Disposal Cup

1: Maximal Barrier Drape™ with 4" fenestration

1: Towel

1: Needle Holder

1: Forceps

1: Safety Scalpel: #11

1: Checklist/CLIP Sheet
- 1: Sterile Procedure Sign

1: Flow Rate Information Card with Injection Log

2: Prep Sponge Swab

2: Gauze Pad: 2" x 2" (5 cm x 5 cm)

5: Gauze Pad: 4" x 4" (10 cm x 10 cm)

1: Dressing: Tegaderm®³ 10 cm x 12 cm

1: Suture: 3-0 Silk with Curved Needle

1: Tray: Prep


1: HemoHopper® Fluid Receptacle
- ¹Licensed under US Patent No. 7,329,412.

²A trademark of Becton, Dickinson and Company.

³A registered trademark of 3M Company.

Not made with natural rubber latex.
Store below 25°C (77°F). Avoid excessive heat above 40°C (104°F).
Contraindications: The Arrowg+ard Blue Plus antimicrobial catheter is contraindicated for patients with known hypersensitivity to chlorhexidine, silver sulfadiazine and/or sulfa drugs.

This catheter contains
**CHLORHEXIDINE and
SILVER SULFADIAZINE**

 Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (16 Ga.)	0.39	2283	10
Medial (18 Ga.)	0.39	913	5
Proximal (18 Ga.)	0.40	996	5

* Priming volumes are approximate and are done without accessories.
† Flow rate values are approximate and are determined using deionized water at 100 cm head height.
** Pressure injection flow rates are determined using media of 11.8 centipoise (cP) viscosity, with 152 cm administration set tubing.

