







(IPNXXXXXX)



Pressure Injectable Arrowg+ard Blue Plus® Two-Lumen CVC



Contents:

- Arrowg+ard Blue Plus®1 Two-Lumen Catheter: 8 Fr. (2.8 mm OD) x 16 cm, Pressure Injectable
- Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - "J" Tip on Other) with Arrow Advancer
- Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer
- Pressure Transduction Probe
- Introducer Needle: Echogenic 18 Ga. x 2-1/2" (6.35 cm) XTW and 5 mL Arrow® Raulerson Spring-Wire Introduction Syringe
- Injection Needle: Eclipse™2 22 Ga. x 1-1/2" (3.81 cm) RW and 5 mL Luer-Slip
- Injection Needle: Eclipse™2 25 Ga. x 1" (2.54 cm) RW and 3 mL Luer-Lock Syringe
- Syringe: 10 mL Luer-Lock
- Tissue Dilator: 9 Fr. (3.0 mm) x 10.2 cm
- SecondSite™ Adjustable Hub: Fastener
- SecondSite™ Adjustable Hub: Catheter Clamp
- SharpsAway® II Locking Disposal Cup
- SharpsAway® Disposal Cup
- Maximal Barrier Drape™ with 4" fenestration
- Needle Holder
- Forceps
- Safety Scalpel: #11
- Checklist/CLIP Sheet
- Sterile Procedure Sign
- Gauze Pad: 2" x 2" (5 cm x 5 cm)

- 5: Gauze Pad: 4" x 4" (10 cm x 10 cm)
- Dressing: Tegaderm®3 10 cm x 12 cm
- Surgical Apparel: Impervious Gown
- Surgical Apparel: Bouffant Cap
- Surgical Apparel: Mask with Eye Shield
- Suture: 3-0 Silk with Curved Needle
- HemoHopper® Fluid Receptacle

¹Licensed under US Patent No. 7,329,412. ²A trademark of Becton, Dickinson and Company

³A registered trademark of 3M Company.









Not made with natural rubber latex.

Store below 25°C (77°F). Avoid excessive heat above 40°C (104°F)

Contraindications: The Arrowg+ard Blue Plus antimicrobial catheter is contraindicated for patients with known hypersensitivity to chlorhexidine, silver sulfadiazine and/or sulfa drugs.

Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
0.68	6350	10 10
	Volume* (mL)	Priming Volume* Rate† (mL) (mL/hr) 0.68 6350

^{*} Priming volumes are approximate and are done without accessories.





LBL053593 R01 (2024-05)

[†] Flow rate values are approximate and are determined using deionized water at 100 cm head

^{**} Pressure injection flow rates are determined using media of 11.8 centipoise (cP) viscosity, with 152 cm administration set tubing.