



REF CS-04306-EJ

6 cm catheter length

1032 inch dia. spring-wire guide

One-Lumen CVC

Contents:

- One-Lumen Catheter: 16 Ga. (1.8 mm OD) x 16 cm Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End "J" Tip on Other) with Arrow Advancer
- Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer Needle

- Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW
 Pressure Transduction Probe
 Arrow® Raulerson Spring-Wire Introduction Syringe: 5 mL

- Tissue Dilator: 7 Fr. (2.3 mm) x 10.2 cm
 Dust Cap: Non-Vented
 SecondSite™ Adjustable Hub: Fastener
 SecondSite™ Adjustable Hub: Catheter Clamp

All components are CE 2797 unless otherwise noted.

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU Not made with natural rubber latex.

Fluid path components are non-pyrogenic.



Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	
Distal (16 Ga.)	0.4	3013	

^{*} Priming volumes are approximate and are done without accessories.



EC REP IDA Business and Technology Park
Dublin Road, Athlone
7797 Co. Westmeath, Ireland

Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA



LBL053807 R01 (2023-11)


















 $[\]dagger$ Flow rate values are approximate and are determined using deionized water at 100 cm head height.