

Contents:

- Arrowg+ard Blue Plus®1 Four-Lumen Catheter: 8.5 Fr. (3.0 mm OD) x 16 cm, 1.
- Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 23-5/8" (60 cm) (Straight Soft Tip on One End - "J" Tip on Other) with Arrow Advancer Origin: XX XXXX
- Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopague over 20 Ga. RW Introducer
- Pressure Transduction Probe Origin: XX XXXX XX XXX XXXXXXX XXXXXXXXXXX
- Introducer Needle: Echogenic 18 Ga. x 2-1/2" (6.35 cm) XTW and 5 mL Arrow® Raulerson Spring-Wire Introduction Syringe Origin: XX XXXX XX XXX
- Injection Needle: Eclipse^{™2} 23 Ga, x 1-1/2" (3.81 cm) and 5 mL Luer-Slip
- Injection Needle: Eclipse^{™2} 25 Ga. x 1" (2.54 cm) and 3 mL Luer-Lock Syringe
- Tissue Dilator: 10 Fr. (3.5 mm) x 10.2 cm Origin: XX XXXX XX XXX XXXXXXX
- XXXXXXXXXXX SecondSite™ Adjustable Hub: Fastener Origin: XX XXXX XX XXX XXXXXXX
- XXXXXXXXXXX SecondSite™ Adjustable Hub: Catheter Clamp Origin: XX XXXX XX XXX
- SharpsAway® II Locking Disposal Cup Origin: XX XXXX XX XXX XXXXXXX XXXXXXXXXXX
- SharpsAway® Disposal Cup Origin: XX XXXX XX XXX XXXXXXX XXXXXXXXXXX

Not made with natural rubber latex.

Store below 25°C (77°F). Avoid excessive heat above 40°C (104°F).

Contraindications: The Arrowg+ard Blue Plus antimicrobial catheter is contraindicated for patients with known hypersensitivity to chlorhexidine, silver sulfadiazine and/or sulfa drugs.

1: Drape: 41" x 55" with 4" fenestration Origin: XX XXXX XX XXX XXXXXXXX XXXXXXXXXXX 1:

- 1. 1: Flow Rate Information Card with Injection Log Origin: XX XXXX XX XXX
- 1.
- 1:
- Gauze Pad: 2" x 2" (5 cm x 5 cm) Origin: XX XXXX XX XXX XXXXXXX 2:
- XXXXXXXXXXX 5: Gauze Pad: 4" x 4" (10 cm x 10 cm) Origin: XX XXXX XX XXX XXXXXXXX
- XXXXXXXXXXX 1: Dressing: Tegaderm®3 10 cm x 12 cm Origin: XX XXXX XX XXX XXXXXXX XXXXXXXXXXX
- 1: Suture: 3-0 Silk with Curved Needle Origin: XX XXXX XX XXX XXXXXXXX XXXXXXXXXXX
- 1: HemoHopper® Fluid Receptacle Origin: XX XXXX XX XXX XXXXXXX XXXXXXXXXXX

¹Licensed under US Patent No. 7,329,412.

- ²A trademark of Becton, Dickinson and Company
- ³A registered trademark of 3M Company.

Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (16 Ga.)	0.38	2781	5
Medial 1 (14 Ga.) Medial 2 (18 Ga.)	0.45 0.35	4980 1453	10 not rated
Proximal (18 Ga.)	0.38	1619	not rated

* Priming volumes are approximate and are done without accessories.

+ Flow rate values are approximate and are determined using deionized water at 100 cm head height.

** Pressure injection flow rates are determined using media of 11.8 centipoise (cP) viscosity, with 152 cm administration set tubing.

LBL053810 R03 (2024-11)