



REF AK-04400

16^{Ga.} 1^{Lumen} 30^{cm catheter length} .032^{inch dia. spring-wire guide}

One-Lumen CVC

Contents:

- 1: One-Lumen Catheter: 16 Ga. (1.8 mm OD) x 30 cm
- 1: Spring-Wire Guide: .032" (0.81 mm) dia. x 23-5/8" (60 cm) (Straight Soft Tip on One End - "J" Tip on Other)
- 1: Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW
- 1: Injection Needle: 25 Ga. x 1" (2.54 cm) and 3 mL Luer-Lock Syringe
- 1: Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer Needle with 5 mL Luer-Slip Syringe
- 1: Injection Needle: 22 Ga. x 1-1/2" (3.81 cm) and 5 mL Luer-Slip Syringe
- 1: Tissue Dilator: 7 Fr. (2.3 mm) x 10.2 cm
- 1: Adapter: Arrow-Johans™ RAECG
- 1: SecondSite™ Adjustable Hub: Fastener
- 1: SecondSite™ Adjustable Hub: Catheter Clamp
- 1: Drape: 24" x 36" (61 cm x 91 cm) with 4" (10 cm) fenestration
- 1: Scalpel: #11
- 2: Prep Sponge Swab
- 3: Gauze Pad: 2" x 2" (5 cm x 5 cm)
- 4: Gauze Pad: 4" x 4" (10 cm x 10 cm)
- 1: Suture: 3-0 Braided Silk with Straight Needle
- 1: Tray: Prep

Rx only

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death.

California Prop. 65

⚠ **WARNING:** Cancer and Reproductive Harm.
www.P65Warnings.ca.gov

Not made with natural rubber latex.

Fluid path components are non-pyrogenic.



Lumen

Priming Volume* (mL)

Gravity Flow Rate† (mL/hr)

Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)
Distal (16 Ga.)	0.3	2224

* Priming volumes are approximate and are done without accessories.

† Flow rate values are approximate and are determined using deionized water at 100 cm head height.



LOT



Arrow International LLC
Subsidiary of Teleflex Incorporated
3015 Carrington Mill Blvd.
Morrisville, NC 27560 USA

Teleflex®
www.teleflex.com

LBL054078 R00 (2021-11)



REF AK-04400

16^{Ga.} 1^{Lumen} 30^{cm catheter length} .032^{inch dia. spring-wire guide}

One-Lumen CVC