



REF EU-14702-N

7 Fr. 2 Lumen

30 cm catheter length

.032 inch dia. spring-wire guide

# Two-Lumen CVC

**Contents:**

- 1: Two-Lumen Catheter: 7 Fr. (2.5 mm OD) x 30 cm
- 1: Spring-Wire Guide, Nitinol, Marked: .032" (0.81 mm) dia. x 26-3/4" (68 cm) (Straight Soft Tip on One End - "J" Tip on Other) with Arrow Advancer with ECG mark
- 1: Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW
- 1: Syringe: 5 mL Luer-Slip
- 1: Tissue Dilator: 8.5 Fr. (2.8 mm) x 10.2 cm
- 1: SecondSite™ Adjustable Hub: Fastener
- 1: SecondSite™ Adjustable Hub: Catheter Clamp

**Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. [www.teleflex.com/IFU](http://www.teleflex.com/IFU)**

**Not made with natural rubber latex.**  
Fluid path components are non-pyrogenic.

All components are CE 2797 unless otherwise noted.



CAS # 7440-48-4

- en
- be
- bg
- hr
- cs
- da
- nl
- et
- fi
- fr
- de
- el
- hu
- is
- it
- lv
- lt
- no
  
- pl
- pt
- ro
- ru
- sr
- sk
- sl
- es
- sv
- tr
- uk



Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)
Distal (16 Ga.)	0.57	1917
Proximal (16 Ga.)	0.62	2000

\* Priming volumes are approximate and are done without accessories.  
† Flow rate values are approximate and are determined using deionized water at 100 cm head height.

EU Authorized Representative and Importer:  
**EC REP** Teleflex Medical  
IDA Business and Technology Park  
Dublin Road, Athlone  
2797 Co. Westmeath, Ireland

Arrow International LLC  
Subsidiary of Teleflex Incorporated  
3015 Carrington Mill Blvd.  
Morrisville, NC 27560 USA

**Teleflex®**  
[www.teleflex.com](http://www.teleflex.com)

LBL054780 R01 (2023-10)

LOT



7 Fr. 2 Lumen

30 cm catheter length

.032 inch dia. spring-wire guide

REF EU-14702-N

# Two-Lumen CVC