



REF EU-15955-N

9.5 Fr. 5 Lumen

20 cm catheter length

.032 inch dia. spring-wire guide

Five-Lumen CVC

Contents:

- 1: Five-Lumen Catheter: 9.5 Fr. (3.3 mm OD) x 20 cm
- 1: Spring-Wire Guide, Nitinol, Marked: .032" (0.81 mm) dia. x 23-5/8" (60 cm) (Straight Soft Tip on One End - "J" Tip on Other) with Arrow Advancer with ECG Mark
- 1: Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW
- 1: Syringe: 5 mL Luer-Slip
- 1: Tissue Dilator: 10 Fr. (3.5 mm) x 10.2 cm
- 1: SecondSite™ Adjustable Hub: Fastener
- 1: SecondSite™ Adjustable Hub: Catheter Clamp

All components are CE 2797 unless otherwise noted.

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU
Not made with natural rubber latex.
 Fluid path components are non-pyrogenic.



Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)
Distal (16 Ga.)	0.48	2988
Medial 1 (14 Ga.)	0.57	4474
Medial 2 (18 Ga.)	0.38	1038
Medial 3 (18 Ga.)	0.38	963
Proximal (18 Ga.)	0.41	1204

* Priming volumes are approximate and are done without accessories.

† Flow rate values are approximate and are determined using deionized water at 100 cm head height.

EU Authorized Representative and Importer:

EC REP
 CE 2797
 Teleflex Medical
 IDA Business and
 Technology Park
 Dublin Road, Athlone
 Co. Westmeath, Ireland

Arrow International LLC
 Subsidiary of Teleflex Incorporated
 3015 Carrington Mill Blvd.
 Morrisville, NC 27560 USA

Teleflex®
www.teleflex.com

LBL054795 (2021-02)

LOT



9.5 Fr. 5 Lumen

20 cm catheter length

.032 inch dia. spring-wire guide

REF EU-15955-N

Five-Lumen CVC