



REF EU-15955-N

20 cm catheter length

Five-Lumen CVC

- Five-Lumen Catheter: 9.5 Fr. (3.3 mm OD) x 20 cm Spring-Wire Guide, Nitinol, Marked: .032" (0.81 mm) dia. x 23-5/8" (60 cm) (Straight Soft Tip on One End "J" Tip on Other) with Arrow Advancer with ECG Mark

- with Arrow Advancer with ELG Mark Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW Syringe: 5 mL Luer-Slip Tissue Dilator: 10 Fr. (3.5 mm) x 10.2 cm SecondSite™ Adjustable Hub: Fastener SecondSite™ Adjustable Hub: Catheter Clamp

All components are CE 2797 unless otherwise noted.

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU Not made with natural rubber latex.

Fluid path components are non-pyrogenic.

























Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	
Distal (16 Ga.)	0.48	2988	
Medial 1 (14 Ga.)	0.57	4474	
Medial 2 (18 Ga.)	0.38	1038	
Medial 3 (18 Ga.)	0.38	963	
Proximal (18 Ga.)	0.41	1204	

^{*} Priming volumes are approximate and are done without accessories.



EU Authorized Representative and Importer:



Teleflex Medical IDA Business and Technology Park
Dublin Road, Athlone
Co. Westmeath, Ireland

Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA



LBL054795 R01 (2023-09)













[†] Flow rate values are approximate and are determined using deionized water at 100 cm head height.